



PLC-1204H1

4 Channel XVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1204H1

04 Channel XVR



Specifications:

Model	PLC-1204H1
Operating System	Embedded LINUX
Encoding Format	H.265
Monitor Quality	VGA, HDMI
Preview Ability	4*1080N@25fps (5 in 1)
Encode Ability	4*1080N @25fps (4 in 1)
Decode Ability	4*1080N@25fps (4 in 1)
Multi-mode Input	Analog: 4*1080N@25fps Hybrid: 2*1080N@25fps (Coaxial)+ 2*1080P@25fps (Network) Network: 4*1080P@25fps
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Smart Function	1CH Item care ,1CH Perimeter detection, Human detection
Audio Compression	4CH Coaxial Audio (Specified camera only)
Intercom	Support
Audio Input	1CH AV Ports (Voice Intercom)
Audio Output	1CH AV Ports (Voice Intercom)
Record Mode	Manual>Alarm>Motion detection>Timing
Local Playback	4CH (Analog input mode)
Search Mode	Search by time, calendar, event, channel
Video Storage	HDD, Network
Backup Mode	Network, USB hard disk, USB burner, SATA burner
Network Connection	Support
Network Protocol	TCP/IP, DHCP, DDNS , PPPOE, SMTP, RTSP, NTP
ONVIF	Support (connect the IPC)
Wireless	3G/4G, Wifi (extend via USB)
Browser	IE/Chrome/Firefox/Safari
APP	Support iPhone, Android
PC	Support
Video Input	4CH BNC
Video Output	1CH VGA, 1ch HDMI

Audio I/O	1/1
Network Interface	RJ45 10M/100M self-adaption
PTZ Control	Support kinds of PTZ protocols(coaxial)
USB	2* USB 2.0 ports
HDD	1*SATA ports (Max 8TB/per)
Language	China/English (Available in more than 20 languages)
Power Supply	12V/2A
Power Consumption	<15W (without HDD)
Working Temperature	-10°C - +60°C,
Working Humidity	10%—90%, Atm:86kpa—106kpa