



## PLC-425M-AI-IR5/PR

Smart AI Bullet 5MP



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



**PLC-425M-AI-IR5/PR**

Smart AI Bullet 5MP


**Specifications:**

<b>Model</b>	<b>PLC-425M-AI-IR5/PR</b>
<b>Image Sensor</b>	1/2.8" SONY Starvis Back-illuminated CMOS sensor
<b>Resolution</b>	5MP
<b>Effective Pixels</b>	2616 (H) x 1964 (V)
<b>Compression</b>	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter Time</b>	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
<b>Minimum Illumination</b>	0.01Lux
<b>S/N Ratio</b>	≥52dB
<b>Scanning System</b>	Progressive
<b>Video Output</b>	Network
<b>Reset Button</b>	Optional
<b>Focus Length</b>	6mm
<b>Focus Control</b>	Fixed
<b>Lens Type</b>	Fixed
<b>Pixels</b>	5MP
<b>Infrared LED</b>	42μ x 4PCS
<b>Infrared Distance</b>	50M
<b>IR Status</b>	Auto Control
<b>IR Power On</b>	Auto Control
<b>Ethernet</b>	RJ-45 (10/100Base-T)
<b>Protocol</b>	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
<b>ONVIF</b>	Support ONVIF 2.4
<b>P2P</b>	YES, Support QR Code
<b>POE</b>	Optional/Internal, Support IEEE 802.3af
<b>Video Delay</b>	0.3S (Within the Lan)
<b>Main Stream 1</b>	2592*1944@20fp 2560*1920@20fp
<b>Main Stream 2</b>	2560*1440@30fp
<b>Main Stream 3</b>	1920*1080@30fps 1280*720@30fps
<b>Sub Stream 1</b>	1280*720@30fps
<b>Sub Stream 2</b>	720*480@30fps

<b>Tri Stream</b>	352*288@30fps
<b>IE Brower</b>	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari (lower than version 12)
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad
<b>Intelligent Analysis</b>	Intrusion Detetion, Line Cross Detetion, Loiter Detetion, People Gather Detecion
<b>Recognition</b>	Face Detection and Recognition (max support 5000 faces)
<b>Day/Night</b>	Colour/ B&W (IR-CUT )
<b>Image Config</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control), Video Tampering
<b>Defog Mode</b>	Support
<b>ROI</b>	Support
<b>BLC</b>	Support
<b>WDR</b>	DWDR: 50dB
<b>Motion Detection</b>	Support
<b>Privacy Masking</b>	3 Rectangular Zone
<b>Recording Mode</b>	NVR/CMS/Web
<b>Language</b>	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
<b>Audio</b>	Optional
<b>SD Card Slot</b>	Optional, Support Max 512GB
<b>Housing</b>	Metal, IP67
<b>Anti-cut Bracket</b>	Optional
<b>IR Cut Filter</b>	YES
<b>Operation Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 950mA
<b>Dimension</b>	220(W) x 105(H) x 109(D)mm
<b>Weight</b>	1650g

**Dimensions:**

