


PLC-332P-IR2  
Dome 2 MP



pöllö 

pöllö 

**Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)

## PLC-332P-IR2

### Dome 2 MP



#### 1. Specifications:

<b>Image Sensor</b>	1/2.9" 2.0 MP HD Color Image Sensor CMOS
<b>Signal System</b>	PAL/NTSC
<b>Horizontal Resolution</b>	2.0 MP (1920 H x 1080 V)
<b>Lens</b>	2.8 mm
<b>IR Range</b>	Up to 20 m IR
<b>Mi. Illumination</b>	Color (0.1 Lux), White and Black (0.01 Lux IR LED on)
<b>Electronic Shutter</b>	1/50 s (1/60 s) - 1/100,000 s, (Auto/Fixed)
<b>Video Output</b>	TVI/AHD/CVI/CVBS Optional, Default Setting: TVI
<b>Exposure</b>	Auto
<b>Auto-gain</b>	Yes
<b>White Balance</b>	Auto
<b>BLC</b>	Auto
<b>Back Light Compensation</b>	Auto
<b>AGC</b>	Yes
<b>Noise Reduction</b>	3 DNR
<b>UTC</b>	Yes
<b>DWDR</b>	Yes
<b>Dimensions</b>	100 mm * 70 mm * 100 mm
<b>S/N Ratio</b>	≥40 dB
<b>Video Output</b>	1.0 Vp - p Composite Output (75Ω/BNC)
<b>Frame Rate</b>	30 fps (60 Hz), 25 fps (50 Hz)
<b>D&amp;N</b>	Supports ICR
<b>Power Consumption</b>	0.4 W (2.5 W After IR LED is Powered on)
<b>Power Supply</b>	DC 12 V (+/-10%)
<b>Ingress Protection</b>	IP65
<b>Working Temperature</b>	-20°C - 50°C, 10% - 90%, (Humidity)
<b>Working Humidity</b>	≤95% RH, No Dew

2. Dimensions:

