



PLC-335P-IR2

Dome 5 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-335P-IR2

Dome 5 MP



1. Specifications:

Image Sensor	1/2.5" 5 MP HD Color Image Sensor CMOS
Signal System	PAL/NTSC
Horizontal Resolution	5 MP (2560 x 1920)
Lens	2.8mm
IR LED	IR Range of 20 m with 12 SMD LED
Min. Illumination	0.01 Lux (IR LED ON), 0.1 Lux (IR LED OFF)
Electronic Shutter	1/50 s (1/60 s) - 1/100,000 s (Auto/Fixed)
Video Output	AHD/TVI, 5 MP, 20fps/12.5fps, AHD/TVI/CVI, 4 MP, 30 fps/25fps
Exposure	Auto
Auto-gain	Yes
White Balance	Auto
BLC	Auto
Gamma Correction	0.45
S/N Ratio	≥50 dB
DNR	2 DNR
Video Output	1.0 Vp - p Composite Output (75 Ω/BNC)
Frame Rate	30 fps (60 Hz), 25 fps (Hz)
D&N	Supports ICR
Power Consumption	1.2 W (4 W After IR LED is Powered on)
Power Supply	DC 12 V (+/-15%)
Working Temperature	-20°C - 50°C, 10% - 90% (Humidity)
Ingress Protection	IP65
Working Humidity	≤95% RH, No Dew
Weight	0.24 kg

2. Dimensions:

