



PLC-422M-IR3/PR

Bullet 2 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-422M-IR3/PR

Bullet 2 MP



Specifications:

Model No.	PLC-422M-IR3/PR
Image Sensor	1/2.8" SONY Starvis CMOS Sensor
Resolution	2 MP 1080p
Effective Pixels	1920 (H) * 1080 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25 - 1/10000 s; NTSC 1/25 - 1/10000 s
Min. Illumination	0.01 Lux
S/N Ratio	≥52 dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Focal Length	3.6 mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	2MP
Infrared LED	14 μ x 20 pcs
Infrared Distance	30 m
IR Status	Auto-control
IR Power On	Auto-control
Ethernet	RJ-45 (10/100 Base - T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Supports ONVIF 2.4
P2P	Yes, Supports QR Code
PoE	Optional, Supports IEEE 802.3af
Video Delay	0.3 s (Within Lan)
Main Stream 1	1920 * 1080 @ 20 fps
Main Stream 2	1280 * 720 @ 20 fps
Sub-stream 1	720 * 480 @ 20 fps
Tri-stream	352 * 288 @ 20 fps

IE Brower	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53), Mac Safari (Lower Than Version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
Day/Night	Color/ Black and White (IR-CUT)
Image Configuration	Saturation/Brightness/Contrast /Sharpness, Mirror, 3 DNR, White Balance, FLK (Flicker Control)
Defog Mode	Yes
BLC	Yes
WDR	DWDR: 50 dB
Motion Detection	Yes
Privacy Masking	3 Rectangular Zones
Recording Mode	NVR/CMS/Web
Languages	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Dutch
Audio	Optional
Housing	Metal
Ingress Protection	IP67
Anti-cut Bracket	Yes
IR Cut Filter	Yes
Operation Temperature	-20 °C - +60 °C RH 95% Max.
Power Source	DC 12 V ± 10%, 900 mA
Dimension	157 (W) x 70 (H) x 66 (D) mm
Weight	650 g

Dimensions:
