



PLC-425M-IR3/PR

Bullet 5 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-425M-IR3/PR

Bullet 5 MP



Specifications:

Model No.	PLC-425M-IR3/PR
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	5 MP (2616 x 1964)
Effective Pixels	2616 (H) x 1964 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25 - 1/10000 s; NTSC 1/25 - 1/10000 s
Min. Illumination	0.01 Lux
S/N Ratio	≥52 dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Focal Length	3.6 mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5 MP
Infrared LED	42 μ x 2 pcs
Infrared Distance	30 m
IR Status	Auto-control
IR Power On	Auto-control
Ethernet	RJ-45 (10/100 Base - T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Supports ONVIF 2.4
P2P	Yes, Supports QR Code
PoE	Optional, Supports IEEE 802.3af
Video Delay	0.3 s (Within Lane)
Main Stream 1	2592 * 1944 @ 20 fps 2560 * 1920 @ 20 fps
Main Stream 2	2560 * 1440 @ 25 fps
Main Stream 3	1920 * 1080 @ 30 fps

	1280 * 720 @ 30 fps
Sub-stream 1	720 * 480 @ 15 fps 720 * 480 @ 30 fps
Tri-stream	352 * 288 @ 15 fps 352 * 288 @ 30 fps
IE Brower	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53), Mac Safari (Lower Than Version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
Day/Night	Color/ Black and White (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3 DNR, White Balance, FLK (Flicker Control)
Corridor Pattern	Yes
Defog Mode	Yes
ROI	Yes
BLC	Yes
WDR	DWDR: 50 dB
Motion Detection	Yes
Privacy Masking	3 Rectangular Zones
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Dutch
Audio	Optional
SD Card Slot	Optional, Supports Max. 128 GB
Housing	Metal
Anti-cut Bracket	Yes
IR Cut Filter	Yes
Operation Temperature	-20 °C - +60 °C RH 95% Max.
Ingress Protection	IP67
Power Source	DC 12 V ± 10%, 700 mA
Dimension	157 (W) x 70 (H) x 66 (D) mm
Weight	650 g

Dimensions:
