



PLC-51264H8/PR

12 MP 64 Channel NVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-51264H8/PR

12 MP 64 Channel NVR



Specifications:

Model No.	PLC-51264H8 PR
Main Processor	ARM Cortex A17 Quad-core Processor
Operating System	Embedded Linux
Input	64 Channel (4096 × 2160, 2592 × 1944, 2048 × 1536, 1920 × 1080, 1280 × 960, 1280 × 720, etc)
Output	1 VGA, 2 HD
Input	1 Port RCA
Output	1 Port RCA (Linear, 1kΩ)
Audio Bit Rate	64 kbps
Audio Compression standard	G.711
Sensor Input	16
Output	4
Motion Detection	64 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, Alarm Output
HD Output 1	4K (3840 × 2160)/60 Hz, 4K (3840 × 2160)/30 Hz, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
HD Output 2	1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA	1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Display Split	64 Channel x D1/36 Channel x D1/25 Channel x D1/16 Channel x D1/9 Channel x D1/4 Channel x D1/1 Channel x 1080p/1 Channel x 3 MP/1 Channel x 4 MP/1 Channel x 5 MP/1 Channel x 4K
Digital Zoom	Yes
OSD	Camera Title, Time, Recording, Motion Detection
Video Compression	H265/H264/H265+/H264+
Resolution	4K (4096 × 2160), 5 MP (2592 × 1944), 4 MP (2688 × 1520), 3 MP (2048 × 1536), 1080p (1920 × 1080), 960p (1280 × 960), 720p (1280 × 720), D1 (720 × 576/720 × 480)
Record Rate	PAL: 12 MP @ 29 × 25 fps, 4K @ 35 × 25 fps, 5 MP @ 58 × 25 fps, 4 MP @ 64 × 25 fps, 3 MP @ 64 × 25 fps, 1080p @ 64 × 25 fps, 960p @ 64 × 25 fps, 720p @ 64 × 25 fps, D1 @ 64 × 25 fps NTSC: 12 MP @ 29 × 30 fps, 4K @ 35 × 30 fps, 5 MP @ 58 × 30 fps, 4 MP @ 64 × 30 fps, 3 MP @ 64 × 30 fps, 1080p @ 64 × 30 fps, 960p @ 64 × 30 fps, 720p @ 64 × 30 fps, D1 @ 64 × 30 fps

Record Mode	Manual/Timer/Motion Detection
Local Sync Playback	4 Channel 4K @ 30 fps, 6 Channel 5 MP @ 30 fps, 8 Channel 4 MP @ 30 fps, 10 Channel 3 MP @ 30 fps, 16 Channel 1080p @ 30 fps, 16 Channel 960p @ 30 fps, 16 Channel 720p @ 30 fps
Decode Capability	4 Channel 4K (3840 × 2160) @ 30 fps
Remote Sync Playback	Yes
Search Mode	All, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast Play, Digital Zoom
Backup Mode	USB Device/Network
Interface	2 RJ-45 10/100/1000 mbps Self-adaptive Ethernet Interfaces
Incoming Bandwidth	350 MB
Network Functions	TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, PoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P
Onvif Version	Supports Onvif 2.4
Web Browser	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53)
CMS Software	Supports Windows 7/Windows 8/Windows 10
Cloud Support (P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
Interface Type	8 SATA Interface
Storage Capacity	Up to 48 TB Capacity
eSATA	1 eSATA interface
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farsi, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces , 1 USB 3.0 Interface
RS485	1 Port, for PTZ Control
Power Supply	100 V - 240 V AC, 50 Hz - 60 Hz
Working Environment	-10°C - 55°C/10 - 90%
Dimension (W × D × H)	2U, 440 mm × 450 mm × 95 mm
Weight	9.8 kg (Without HDD)

Dimensions:

