

Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368 Email: info@pollo.net.au Website: www.pollo.net.au





PLC-554H1

5 MP 4 Channel NVR



1. Features:

- Using cloud services, easily achieve a variety of network penetration options; one step to achieve remote monitoring.
- Device supports mobile phone remote monitoring options (iPhone /Android).
- Device supports VGA and HDMI outputs simultaneously.
- Device comes with powerful network services (supports DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP Competence, IP Search, Alarm Center, Perfect Matching (WEB, Client, SDK, and Easy-to-achieve mutual communication).
- Device supports more than 20 kinds of languages (Arabic, Brazilian, Bulgarian, Czech, Dutch, English, Persian, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Polish, Portuguese, Romanian, Russian, Chinese Simplified, Slovak, Spanish, Swedish, Thai, Chinese Traditional, Turkish, and Vietnamese). There are no language restrictions. There is free replacement for boot interface and free selection for interface style.

2. Model Support:

CHANNEL		CHANNEL MODE Digital Channel	Playback
	No.	Channel * Resolution/fps	Channel * Resolution/fps
4 Channel	1	4 * 5M/25	1 * 5M/25 (Main Stream) 4 * D1/25 (Second Stream)



4. Specifications:

System	Video Compression	H.265
	Operating	Embedded Linux
	VGA Output	Yes
Video	Loop	No
	HDMI Output	Yes
Audio	Audio Input	No
	Audio Out	No
	Intercom	Yes
Record	Channel Number of Real-time Recording	4 Channel
	Recording Mode	Schedule, Manual, Motion, External Alarm
Playback	Simultaneous Playback	4 Channel
	Search Mode	Time, Calendar, Event, Channel
Backup	USB HDD/U-disk	Yes
	USB DVD Burner	Yes
	Backup File Format	DAV, AVI
	Browsers	Yes, Supports IE
Remote	VMS	Yes, Supports VMS
Access	Mobile Phone Operating System	IPhone, Android
	Users	Max 32, (Cloud Forward 32 Channel)
Alarm	Alarm Input	None
	Alarm Output	None
Storage Capacity	HDD Number	1 pcs Max. 6 TB
	E-SATA	No
	Ethernet Port	10/100 Mbps Ethernet (RJ-45)
	Network Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
	Remote Control	Yes (Optional)
Other	Power Supply	DC 12 V/2 A
	Working Temperature	-10°C - 60°C
	Humidity	10% - 90%



5. Dimensions:



