



## **PLC-5508H1**

5 MP 08 Channel NVR



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



# PLC-5508H1

## 5 MP 08 Channel NVR



### 1. Features

- ✔ Using cloud services, easily achieve a variety of network penetration options; one step to achieve remote monitoring.
- ✔ Device supports mobile phone remote monitoring options (iPhone /Android).
- ✔ Device supports VGA and HDMI outputs simultaneously.
- ✔ Device comes with powerful network services (supports DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP Competence, IP Search, Alarm Center, Perfect Matching (WEB, Client, SDK, Easy-to-achieve mutual communication).
- ✔ Device supports more than 20 kinds of languages (Arabic, Brazilian, Bulgarian, Czech, Dutch, English, Persian, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Polish, Portuguese, Romanian, Russian, Chinese Simplified, Slovak, Spanish, Swedish, Thai, Chinese Traditional, Turkish, Vietnamese). There are no language restrictions. There is free replacement for boot interface and free selection for interface style.

### 2. Model Support:

CHANNEL	CHANNEL MODE		Playback
	N0.	Digital Channel	
		Channel * Resolution/fps	Channel * Resolution/fps
8 Channel	1	8 * 5M/25	1 * 5M/25 (Main Stream) 8 * D1/25 (Second Stream)

### 3. Specifications:

<b>System</b>	Video Compression	H.265
	Operating	Embedded Linux
<b>Video</b>	VGA Output	Yes
	Loop	No
	HDMI Output	Yes
<b>Audio</b>	Audio Input	No
	Audio Out	No
	Intercom	Yes
<b>Record</b>	Channel Number of Real-time Recording	8 * 5M/25
	Recording Mode	Schedule, Manual, Motion, External Alarm
<b>Playback</b>	Simultaneous Playback	8 Channel
	Search Mode	Time, Calendar, Event, Channel
<b>Backup</b>	USB HDD/U-disk	Yes
	USB DVD Burner	Yes
	Backup File Format	DAV, AVI
<b>Remote Access</b>	Browsers	Yes, Supports above IE 6.0
	VMS	Yes, Supports VMS
	Mobile Phone Operating System	IPhone, Android
	Users	Max. 32, (Cloud Forward 32 Channel)
<b>Alarm</b>	Alarm Input	None
	Alarm Output	None
<b>Storage Capacity</b>	HDD Number	1 pcs
	E-SATA	No
<b>Network Other</b>	Ethernet Port	60 Mbps
	Network Protocol	60 Mbps
	Remote Control	10/100 Mbps Ethernet (RJ-45)
	Power Supply	TCP/IP, DHCP, DDNS, NTP, SMTP, RTSP
	Working Temperature	Yes (Optional)
<b>Other System</b>	Humidity	DC 12 V/2A
	Video Compression	-10°C - 60°C
	Operating	10% - 90%

4. Dimensions

