



PLC-5516H1

5 MP 16 Channel NVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-5516H1

5 MP 16 Channel NVR



Features

- ✔ Using cloud services, easily achieve a variety of network penetration options; one step to achieve remote monitoring.
- ✔ Device supports mobile phone remote monitoring options (iPhone /Android).
- ✔ Device supports VGA and HDMI outputs simultaneously.
- ✔ Device comes with powerful network services (supports DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP Competence, IP Search, Alarm Center, Perfect Matching (WEB, Client, SDK, Easy-to-achieve mutual communication).
- ✔ Device supports more than 20 kinds of languages (Arabic, Brazilian, Bulgarian, Czech, Dutch, English, Persian, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Polish, Portuguese, Romanian, Russian, Chinese Simplified, Slovak, Spanish, Swedish, Thai, Chinese Traditional, Turkish, Vietnamese). There are no language restrictions. There is free replacement for boot interface and free selection for interface style.

2. Model Support:

CHANNEL	CHANNEL MODE		Playback
	NO.	Digital Channel	
16 Channel	1	Channel * Resolution/fps 16 * 5M/25	Channel * Resolution/fps 1 * 5M/25 (Main Stream) 16 * D1/25 (Second Stream)

3. Specifications

System	Video Compression	H.265
	Operating	Embedded Linux
Video	VGA Output	Yes
	Loop	Yes
Audio	HDMI Output	No
	Audio Input	No
	Audio Out	Yes
Record	Intercom	16 * 5M/25 fps
	Channel Number of Real-time Recording	Schedule, Manual, Motion, External Alarm
Playback	Recording Mode	16 Channel
	Simultaneous Playback	Time, Calendar, Event, Channel
Backup	Search Mode	Yes
	USB HDD/U-disk	Yes
	USB DVD Burner	DAV, AVI
Remote Access	Backup File Format	Yes, Supports Above IE 6.0
	Browsers	Yes, Supports VMS
	VMS	IPhone, Android
	Mobile Phone Operating System	Max. 32, (Cloud Forward 32 Channel)
Alarm	Users	None
	Alarm Input	None
Storage Capacity	Alarm Output	1 pc Max. 6 TB
	HDD Number	No
Network	E-SATA	256 Mbps
	Ethernet Port	256 Mbps
	Network Protocol	10/100 Mbps Ethernet (RJ-45)
	Remote Control	TCP/IP, DHCP, DDNS, NTP, SMTP, RTSP
	Power Supply	Yes
Power/Working Temperature	Working Temperature	DC 12 V/2A
	Humidity	-10°C - 60°C
	Video Compression	10% - 90%

4. Dimensions:

