



## **PLC-5532H4**

32 Channel NVR



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



# PLC-5532H4

## 32CH NVR



### Features

- ✔ Using cloud services, easily achieve a variety of network penetration; one step to achieve remote monitoring,
- ✔ Support mobile phone remote monitoring (iPhone /Android)
- ✔ Supports VGA and HDMI output simultaneously
- ✔ Powerful Network Services (Support DHCP、PPPOE、FTP、DNS、DDNS、NTP、UPNP、EMAIL、IP Competence、IP Search、Alarm Center), Perfect matching (WEB、Client、SDK), Easy to achieve mutual-communication
- ✔ More than 20 kinds of languages supported (Arabic、Brazilian、Bulgarian、Czech、Dutch、English、Persian、Finnish、French、German、Greek、Hebrew、Hungarian、Indonesian、Italian、Japanese、Polish、Portuguese、Romanian、Russian、Chinese Simplified、Slovak、Spanish、Swedish、Thai、Chinese Traditional、Turkish、Vietnamese), no language restrictions
- ✔ Free replacement for boot interface and free selection for interface style

### Model Support:

CHANNEL	CHANNEL MODE Digital channel		Playback
	NO.	Channel * Resolution/fps	Channel *Resolution/fps
32CH	1	32 * 5M/25	4 * 5M/25 (main stream)

**Specification:**

<b>System</b>	Video Compression	H.265
	Operating	Embedded Linux
<b>Video</b>	VGA output	Yes
	HDMI output	Yes
<b>Audio</b>	Audio input	NO
	Audio out	Yes
	Intercom	yes
<b>Record</b>	Channel number of real-time recording	32ch * 5M/25 fps
	Recording mode	Schedule, Manual, Motion, External Alarm
<b>Playback</b>	Simultaneous playback	4CH* 5M/25 fps
	Search mode	Time, Calendar, Event, Channel
<b>Backup</b>	USB HDD /U-disk	YES
	USB DVD Burner	YES
	Backup file format	DAV、AVI
<b>Remote Access</b>	Browsers	YES, supports above IE 6.0
	VMS	YES, supports VMS
	Mobile phone operating system	IPhone, Android
	Users	Max 32, (Cloud Forward 32ch)
<b>Alarm</b>	Alarm input	None
	Alarm output	None
<b>Storage</b>	HDD number	4 pcs Max 8TB
	E-SATA	NO
<b>Network</b>	Input bandwidth	320Mbps
	Input bandwidth	320Mbps
	Ethernet port	10/ 1000 Mbps Ethernet (RJ-45)
	Network protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, RTSP.
	Remote control	yes
<b>Other</b>	Power supply	DC12V 6A
	Working temperature	-10°C ~60°C
	Humidity	10% ~ 90%

**Dimensions:**

