



**PLC-9536-IR25/PR**  
36X Speed Dome 5 MP



**Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-9536-IR25/PR

36X Speed Dome 5 MP



### Specifications:

<b>Model</b>	<b>PLC-9536-IR25/PR</b>
<b>Image Sensor</b>	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
<b>Horizontal Resolution</b>	5 MP
<b>Compression</b>	H.264/H.265
<b>S/N Ratio</b>	>50 dB
<b>Horizontal Rotation Speed</b>	200°/s
<b>Horizontal Rotation Range</b>	0° - 360°
<b>Tilt Rotation Speed</b>	100°/s
<b>Tilt Rotation Range</b>	0° - 90°
<b>Preset Points</b>	220
<b>Guard Tours</b>	3 Groups
<b>Guard Points</b>	Max. 16 Points
<b>Focal Length</b>	4.6 mm - 165 mm
<b>Focus Control</b>	36X Optical Zoom
<b>Infrared LED</b>	∅ 42 x 8 pcs IR LEDS + 4 pcs LED Laser
<b>IR Range</b>	250 m
<b>Day-night Mode</b>	Auto
<b>Network Protocol</b>	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
<b>ONVIF</b>	Yes
<b>Network interface</b>	Built-in RJ45 Network Interface, Supports 10M/100M IP DATA
<b>Stream type</b>	Main Stream/Sub-stream/MJPEG
<b>Audio</b>	Optional
<b>Alarm</b>	Optional
<b>PoE</b>	N/A
<b>Ingress Protection</b>	IP67
<b>Operating Temperature</b>	Indoor: 0° - +40°, Outdoor: -40° - +60°
<b>Operating Humidity</b>	≤90% Non-condensing
<b>Power</b>	DC 12 V/4 A
<b>Lightning Protection</b>	Transient Voltage 6000 V
<b>Dimension</b>	33 x 33 x 52 (cm)
<b>Weight</b>	13.7 kg

Dimensions:

