



PLC-1204H1/PR

2 MP 04 Channel XVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1204H1/PR

2 MP 04 Channel XVR



Specifications:

Model	PLC-1204H1/PR
Main Processor	HI3520DV200
Operating System	Embedded Linux
Input	Analog: 4 * 1080p Analog + Network: 2 * Analog (1080p) + 4 * Network Network: 9 * 1080p/960p/720p (Total Incoming Bandwidth ≤46 Mbps)
Input	4 Channel BNC
Signal Type	CVBS/AHD/CVI/TVI 2.0/Network
Output	1 HD, 1 VGA
Input	4 Channel, RCA
Two-way Audio	No
Output	1 Channel, RCA
Sensor Input	No
Output	No
Motion Detection	4 Channel (Max. 9 Channel in Pure Network Mode)
Trigger Events	Recording, Email, Screen Tips, Buzzer, Push Notifications (Motion Detection)
Email Alarm	Send Image to Designated E-mail
Interface	RS485
Protocol	Pelco - D, Pelco - P
Baud Rate	110 - 921600
Address	0 - 255
VGA	Resolution: 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
HD Output	Resolution: 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Display Split	9 Channel/4 Channel/1 Channel
Privacy Masking	3 Rectangular Zones (Each Camera)
OSD	Camera Title, Time, Video Loss, Alarm, Motion Detection, Recording
Video Compression	H.264
Audio Compression	G.711u
Resolution	Half 1080p (960 × 1080), 720p (1280 × 720), 960H (P: 960 × 576/N: 960 × 480)
Video Quality	Worst/Worse/Ordinary/Well/Best
Record Rate	Analog: Half 1080p (960 x 1080, 4 * 25 fps), 720p (1280 × 720, 4 * 25 fps), 960H (P: 960 × 576, 4 * 25 fps/N: 960 × 480, 4 * 30 fps) Pure IP: PAL: 1080p @ 9 x 25 fps, 960p @ 9 x 25 fps, 720p @ 9 x 25 fps, D1 @ 9 x 25 fps NTSC: 1080p @ 9 x 30 fps, 960p @ 9 x 30 fps, 720p @ 9 x 30 fps, D1 @ 9 x 30 fps
Record Mode	Manual/Timer/Motion Detection

Decode Capability	2 Channel 1080p @ 30 fps
Sync Playback	Pure Analog: 4 Channel 1080N @ 25 fps Mixture Mode: 1 Channel 1080p @ 30 fps + 1 Channel 1080N @ 25 fps Pure Network: 2 Channel 1080p @ 30 fps, 3 Channel 960p @ 30 fps, 4 Channel 720p @ 30 fps
Remote Playback	1 Channel
Search Mode	All, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast Play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device (Format FAT 32)/Network/FTP
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P
DDNS	DynDNS, Change-IP, No-IP, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53)
CMS Software	Supports Windows 7/ Windows 8/Windows 10
Extra Stream	CIF (1 - 25 fps)
Smart Phone	iPhone, iPad, Android, Android Pad
Interface Type	1 SATA Interface
Storage Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 6 TB)
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farsi, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
UTC Control	Yes
USB Interface	2 USB 2.0 Interfaces
Power Consumption	DC 12 V ≤6 W (Without Hard Disk)
Working Environment	-10 °C - 55 °C/10 - 90%
Dimension (W×D×H)	260 * 215 * 43 (mm)
Weight	2 kg (Without HDD)

Dimensions:

