



PLC-1204H1

2 MP 04 Channel XVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1204H1

2 MP 04 CHANNEL XVR



1. Features:

- ✔ The user can easily achieve a variety of network penetration using cloud services. They can monitor remotely with ease and convenience. No complex network settings are required.
- ✔ The device supports mobile phone remote monitoring options (iPhone /Android).
- ✔ The device supports multiple web browsers (IE, Chrome, Firefox etc.).
- ✔ The device also supports VGA, TV and HDMI output simultaneously.
- ✔ The device comes with powerful network services (supports DHCP, PPPoE, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP Competence, IP Search, Alarm Center), perfect matching (WEB, Client, SDK). The device aids in better inter-connectivity between devices.
- ✔ The device also supports option for over 20 kind of languages (Arabic, Brazilian, Bulgarian, Czech, Dutch, English, Persian, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Polish, Portuguese, Romanian, Russian, Chinese Simplified, Slovak, Spanish, Swedish, Thai, Chinese Traditional, Turkish and Vietnamese).

2. Main Board configuration:

DSP	RAM	HDD
3520DV200	2 GB	1 * 6 TB

3. Support Model:

MODEL	CHANNEL MODE (Analog Channel + Digital channel)		Playback
	NO.	Channel * Resolution/fps	Channel * Resolution/fps
4 CHANNEL	1	4 * 1080n/25 + 0	4 * 1080n/6
	2	2 * 1080n/25 + 2 * 1080p/25	1 * 1080p/25
	3	0 + 4 * 1080p/25	1 * 1080p/25

4. Specifications:

System	Video Compression	H.264
	Operating	Embedded Linux
Video	Input	4 Channel
	VGA Output	Yes
	CVBS Output	Yes
	Loop Output	No
	HDMI Output	Yes
Audio	Audio Input	1 Channel Audio in
	Audio Out	1 Channel Audio out
	Intercom	No
Fan	Fan	No
Recording	Recording Mode	Schedule, Manual, Motion
Playback	Simultaneous Playback	1 Channel
	Search Mode	Time, Calendar, Event, Channel
Backup	USB HDD/U-disk	Yes
	USB DVD Burner	Yes
	Backup File Format	AVI
Remote Access	Browsers	Yes, Supports Multiple Web Browsers
	CMS	Yes, Supports Pollo View
	Mobile Phone Operating System	IPhone, Android
Alarm	Alarm Input	N/A
	Alarm Output	N/A
Storage Capacity	HDD Number	1 SATA, Max. 6 TB
	E-SATA	No
PTZ	Connector	No
	Protocol	PELCOP, PELCOD, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
	Control Mode	Pan, Tilt, Zoom, Preset, Cruise, Trace
Network	Ethernet Port	10/100 Mbps Ethernet (RJ-45)
	Network Protocol	TCP/IP, DHCP, NTP, SMTP
Other	Remote Control	No
	Power Supply	12 V, 2A POWER
	Working Temperature	-10°C - 60°C
	Humidity	10% - 90% Humidity
	Weight	1.25 kg