



## **PLC-1208H1/PR**

2 MP 08 Channel XVR



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-1208H1/PR

2 MP 08 Channel XVR



### Specifications:

Model	PLC-1208H1/PR
Main Processor	HI3520DV400
Operating System	Embedded Linux
Input	Analog: 8 * 1080p Analog + Network: 2 * Analog (1080p) + 4 * Network Network: 9 * 1080p/960p/720p (Total Incoming Bandwidth ≤46 Mbps)
Input	8 Channel BNC
Signal Type	CVBS/AHD/CVI/TVI 2.0/Network
Output	1 HD, 1 VGA
Input	8 Channel, RCA
Two-way Audio	No
Output	4 Channel, RCA
Sensor Input	No
Output	No
Motion Detection	8 Channel (Max. 12 Channel in Pure Network Mode)
Trigger Events	Recording, Email, Screen Tips, Buzzer, Push Notifications (Motion Detection)
Email Alarm	Send Image to Designated E-mail
Interface	RS485
Protocol	Pelco - D, Pelco - P
Baud Rate	110 - 921600
Address	0 - 255
VGA	Resolution: 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
HD Output	Resolution: 3840 × 2160/30 Hz, 2560 × 1440/30 Hz, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Display Split	16 Channel/9 Channel/8 Channel/4 Channel /1 Channel
Privacy Masking	3 Rectangular Zones (Each Camera)
OSD	Camera Title, Time, Video Loss, Alarm, Motion Detection, Recording
Video Compression	H.265+/H.265/H.264+/H.264
Audio Compression	G711u
Resolution	Half 1080p (960 × 1080), 720p (1280 × 720), 960H (P: 960 × 576/N: 960 × 480)
Video Quality	Worst/Worse/Ordinary/Well/Best

<b>Record Rate</b>	Analog: Half 1080p (960 × 1080, 8 * 15 fps), 720p (1280 × 720, 8 * 15 fps), 960H (P: 960 × 576, 8 * 22 fps/N: 960 × 480, 8 * 22 fps) Pure IP (H.265): PAL: 5 MP @ 8 × 25 fps, 4 MP @ 12 × 25 fps, 3 MP @ 12 × 25 fps, 1080p @ 12 × 25 fps, 960p @ 12 × 25 fps, 720p @ 12 × 25 fps, D1 @ 12 × 25 fps NTSC: 5 MP @ 8 × 30 fps, 4 MP @ 12 × 30 fps, 3 MP @ 12 × 30 fps, 1080p @ 12 × 30 fps, 960p @ 12 × 30 fps, 720p @ 12 × 30 fps, D1 @ 12 × 30 fps
<b>Record Mode</b>	Manual/Timer/Motion Detection
<b>Decode Capability</b>	2 Channel 1080p @ 30 fps
<b>Sync Playback</b>	Pure Analog: 8 Channel 1080N @ 15 fps Mixture Mode: 1 Channel 5 MP @ 30 fps, 2 Channel 1080p @ 30 fps Pure Network: 1 Channel 5 MP @ 30 fps, 2 Channel 1080p @ 30 fps
<b>Remote Playback</b>	4 Channel/1 Channel
<b>Search Mode</b>	All, Channel, Manual, Time, Date, Motion Detection
<b>Playback Functions</b>	Play, Pause, Stop, Fast Play, Rewind, Digital Zoom, Full screen
<b>Smart Phone Playback</b>	4 Channel
<b>Backup Mode</b>	USB Device (Format FAT 32)/Network/FTP
<b>Interface</b>	1 RJ45 10M/100M Adaptive Ethernet Interface
<b>Network Functions</b>	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P
<b>DDNS</b>	DynDNS, Change-IP, No-IP, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
<b>Web Browser</b>	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53)
<b>CMS Software</b>	Supports Windows 7/ Windows 8/Windows 10
<b>Extra Stream</b>	CIF (1 - 25 fps)
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad
<b>Interface Type</b>	1 SATA Interface
<b>Storage Capacity</b>	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8 TB)
<b>Language</b>	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farsi, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
<b>UTC Control</b>	Yes
<b>USB Interface</b>	2 USB 2.0 Interfaces
<b>Power Consumption</b>	DC 12 V ≤6W (Without Hard Disk)
<b>Working Environment</b>	-10 °C - 55 °C/10 - 90%
<b>Dimension (W×D×H)</b>	260 * 215 * 43 (mm)
<b>Weight</b>	2 kg (Without HDD)

**Dimensions:**

