



## PLC-1232H8/PR

2 MP 32 Channel XVR



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-1232H8/PR

### 2 MP 32 Channel XVR



#### Specifications:

<b>Model</b>	<b>PLC-1232H8/PR</b>
<b>Operating System</b>	Embedded Linux
<b>Input</b>	Analog: 32 * 1080p Analog + Network: 30 * Analog (1080p) + 2 * Network (Max. 8 MP), 28 * Analog (1080p) + 4 * Network (Max. 8 MP), 26 * Analog (1080p) + 6 * Network (Max. 8 MP), 24 * Analog (1080p) + 8 * Network (Max. 8 MP), 22 * Analog (1080p) + 10 * Network (Max. 8 MP), 20 * Analog (1080p) + 12 * Network (Max. 8 MP), 18 * Analog (1080p) + 14 * Network (Max. 8 MP), 16 * Analog (1080p) + 16 * Network (Max. 8 MP) 14 * Analog (1080p) + 18 * Network (Max. 8 MP), 12 * Analog (1080p)+20 * Network (Max. 8 MP), 10*Analog(1080P) + 22 * Network (Max. 8 MP) 8 * Analog (1080p) + 24 * Network (Max. 8 MP), 6 * Analog (1080p) + 26 * Network (Max. 8 MP), 4 * Analog (1080p) + 28 * Network (Max. 8 MP) 2 * Analog (1080p) + 30 * Network (Max. 8 MP) Network: 32 * Network (Max. 8 MP) (Total Incoming Bandwidth ≤160 Mbps)
<b>Input</b>	32 Channel BNC
<b>Signal Type</b>	CVBS/AHD/CVI/TVI 2.0/Network
<b>Output</b>	1HD, 1 VGA, 1 CVBS
<b>Audio Input</b>	12 Channel, RCA
<b>Output</b>	1 Channel, RCA
<b>Sensor Input</b>	16 Channel
<b>Output</b>	4 Channel
<b>Motion Detection</b>	32 Channel
<b>Trigger Events</b>	Recording, Email, Screen tips, Buzzer, Push Notifications (Motion Detection)
<b>Email Alarm</b>	Send Image to Designated E-mail
<b>Interface</b>	RS485
<b>Protocol</b>	Pelco - D, Pelco - P
<b>Baud Rate</b>	110 - 921600
<b>Address</b>	0 - 255
<b>VGA</b>	Resolution: 1920 × 1080p /60 Hz, 1280 × 1024 /60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>HD Output</b>	Resolution: 3840 × 2160/30 Hz, 2560 x 1440/30 Hz, 1920 × 1080p /60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>Display Split</b>	32 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel/1 Channel

<b>Privacy Masking</b>	3 Rectangular Zones (Each Camera)
<b>OSD</b>	Camera Title, Time, Video Loss, Alarm, Motion Detection, Recording
<b>Video Compression</b>	H.265/H.265+/H.264+/H.264
<b>Audio Compression</b>	G.711u
<b>Resolution</b>	Half 1080p (960 × 1080), 720p (1280 × 720), 960H (P: 960 × 576/N: 960 × 480)
<b>Video Quality</b>	Worst/Worse/Ordinary/Well/Best
<b>Record Rate</b>	Analog: PAL: Half 1080p (960 x 1080, 32 * 15 fps), 720p (1280 × 720, 32 * 15 fps), 960H (960 × 576, 32 * 22 fps) NTSC: Half 1080p (960 x 1080, 32 * 15 fps), 720p (1280 × 720 32 * 15 fps), 960H (960 × 480, 32 * 22 fps) Pure IP (H.265): PAL: 8 MP @ 17 × 25 fps, 5 MP @ 26 × 25 fps, 4 MP @ 32 × 25 fps, 3 MP @ 32 × 25 fps, 1080p @ 32 × 25 fps, 960P @ 32 × 25 fps, 720p @ 32 × 25 fps, D1 @ 32 × 25 fps NTSC: 8 MP @ 17 × 30 fps, 5 MP @ 26 × 30 fps, 4 MP @ 32 × 30 fps, 3 MP @ 32 × 30 fps, 1080p @ 32 × 30 fps, 960p @ 32 × 30 fps, 720p @ 32 × 30 fps, D1 @ 32 × 30 fps
<b>Record Mode</b>	Manual/Timer/Motion Detection/Alarm
<b>Decode Capability</b>	9 Channel 1080p @ 30 fps
<b>Sync Playback</b>	Pure Analog: 32 Channel 1080N @ 15 fps Mixture Mode: 1 Channel 8 MP @ 30 fps, 1 Channel 5 MP @ 30 fps, 2 Channel 4 MP @ 30 fps, 3 Channel 3 MP @ 30 fps, 4 Channel 1080p @ 30 fps, 4 Channel 1080N @ 12 fps Pure Network: 2 Channel 8 MP @ 30 fps, 3 Channel 5 MP @ 30 fps, 4 Channel 4 MP @ 30 fps, 5 Channel 3 MP @ 30 fps, 9 Channel 1080p @ 30 fps
<b>Remote Playback</b>	4 Channel/1 Channel
<b>Search Mode</b>	All, Channel, Manual, Time, Date, Motion Detection
<b>Playback Functions</b>	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
<b>Smart Phone Playback</b>	4 Channel
<b>Backup Mode</b>	USB Device (Format FAT 32)/Network/FTP
<b>Interface</b>	1 RJ45 10M/100M/1000M Adaptive Ethernet Interface
<b>Network Functions</b>	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P
<b>DDNS</b>	DynDNS, Change-IP, No-IP, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
<b>Web Browser</b>	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53)
<b>CMS Software</b>	Supports Windows XP/Windows Vista/Windows 7/Windows 8
<b>Extra Stream</b>	CIF/D1 (1 - 22 fps)
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad
<b>Interface Type</b>	8 SATA Interface
<b>Storage Capacity</b>	8 SATA Hard Disk (3.5" SATA, Up to 64 TB) + 1 E-SATA Interface (Up to 8 TB)
<b>Language</b>	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farsi German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
<b>UTC Control</b>	Yes
<b>USB Interface</b>	2 USB 2.0 Interfaces

<b>Power consumption</b>	AC 115 - 230 V ≤35 W (Without HDD)
<b>Working Environment</b>	-10 °C - 55 °C/10 - 90%
<b>Dimension (W × D × H)</b>	440 * 450 * 95 (mm)
<b>Weight</b>	9.8 kg (Without HDD)

**Dimensions:**

