



PLC-1504H1

5 MP 4 Channel XVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1504H1

5 MP 4 Channel XVR



1. Features:

- ❖ Device comes with H.265 video compression.
- ❖ Using cloud services, you can easily achieve a variety of network penetration; one step to achieve remote monitoring. There is no need of various complicated network settings.
- ❖ Device supports mobile phone remote monitoring options (iPhone /Android).
- ❖ Device supports multiple web browsers (IE, Chrome, Firefox etc.).
- ❖ Device supports VGA, TV and HDMI output simultaneously.
- ❖ Device comes with powerful network services (supports DHCP, PPPoE, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP Competence, IP Search, Alarm Center), perfect matching (Web, Client, SDK). It is easy to achieve mutual-communication among devices.
- ❖ Device supports option for over 20 kind of languages (Arabic, Brazilian, Bulgarian, Czech, Dutch, English, Persian, Finnish, French, German, Greek, Hebrew, Hungarian, Indonesian, Italian, Japanese, Polish, Portuguese, Romanian, Russian, Chinese Simplified, Slovak, Spanish, Swedish, Thai, Chinese Traditional, Turkish and Vietnamese).

2. Specifications:

System	Video Compression	H.265
	Operating System	Embedded Linux
Video	Channels Input	4 Channel
	VGA Out Resolution	1440 * 900, 1280 * 1024, 1280 * 768, 1280 * 720
	HDMI Output Resolution	3840 * 2160, 2560 * 1440, 2048 * 1440, 1920 * 1080, 1440 * 900, 1280 * 1024, 1280 * 768, 1280 * 720
	BNC Output	Yes
Audio	Audio Input	4 Channel
	Audio Out	1 Channel Output
	Intercom	Yes
Decoding	Encoding	4 * 5M/ 6
	Synchronous Playback	2* 5M/ 6
Network	Network Protocol	TCP/IP, DHCP, Cloud, P2P, DDNS, NTP, SMTP
Backup	USB HDD/U-disk	Yes
	USB DVD Burner	Yes
	Backup File Format	DAV, AVI
Remote Access	Browsers	Yes, Supports Multiple Web Browsers
	CMS	Yes, Supports CMS3.0
	Mobile Phone OS	iPhone, Android
Alarm	Alarm Input	No (Optional 4 Channel)
	Alarm Output	1 Channel
	Buzzer	Yes
Storage Capacity	HDD Number	1 * 6 TB
	E-SATA	No
PTZ	Protocol	PELCOP, PELCOD, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
	Control Mode	Pan, Tilt, Zoom, Preset, Cruise, Trace
	UTC Protocol	HD-AHD, HD-FH, HD-HXST, HD-MY, HD-TVI
External Interface	Network Interface	10/100 Mbps Ethernet (RJ-45)
	Serial Interface	1 RS-485
	USB Interface	2 * USB 2.0
Other	Remote Control	Yes
	Power Supply	DC 12 V/2A
	Working Temperature	-10°C - 60°C
	Humidity	10% - 90% Humidity
	Dimensions	258.4 x 230.5 x 44.5

3. Dimensions:

