



## PLC-1508H1-E

8 Channel XVR



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



# PLC-1508H1-E

08 Channel XVR



## Specifications:

<b>Model</b>	PLC-1508H1-E
<b>Operating System</b>	Embedded LINUX
<b>Encoding Format</b>	H.265
<b>Monitor Quality</b>	VGA, HDMI
<b>Preview Ability</b>	8*5M-N @20fps (5 in 1), 8*1080P@25fps
<b>Encode Ability</b>	8*5M-N @12fps (4 in 1), 8*1080P@18fps
<b>Decode Ability</b>	8*5M-N @12fps (4 in 1), 8*1080P@18fps
<b>Multi-mode Input</b>	Analog: 8*5M-N@8fps Hybrid: Support any channel mode combination (1080N Analog + 1080P digital) Network: 8*1080P@25fps
<b>Motion Detection</b>	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
<b>Audio Compression</b>	8CH Coaxial Audio (Specified camera only)
<b>Intercom</b>	Support
<b>Audio Input</b>	1CH AV Ports (Voice Intercom)
<b>Audio Output</b>	1CH AV Ports (Voice Intercom)
<b>Record Mode</b>	Manual>Alarm>Motion detection>Timing
<b>Local Playback</b>	8CH (Analog input mode)
<b>Search Mode</b>	Search by time, calendar, event, channel
<b>Video Storage</b>	HDD, Network
<b>Backup Mode</b>	Network, USB hard disk, USB burner, SATA burner
<b>Network Connection</b>	Support
<b>Network Protocol</b>	TCP/IP, DHCP, DDNS, PPPOE, SMTP, RTSP, NTP
<b>ONVIF</b>	Support (connect the IPC)
<b>Wireless</b>	3G/4G, Wifi (extend via USB)
<b>Browser</b>	IE/Chrome/Firefox/Safari
<b>APP</b>	Support iPhone, Android
<b>PC</b>	Support
<b>Video Input</b>	8CH BNC
<b>Video Output</b>	1CH VGA, 1ch HDMI

<b>Audio I/O</b>	1/1
<b>Network Interface</b>	RJ45 10M/100M self-adaption
<b>PTZ Control</b>	Support kinds of PTZ protocols(coaxial)
<b>USB</b>	2* USB 2.0 ports
<b>HDD</b>	1*SATA ports (Max 8TB/per)
<b>Language</b>	China/English (Available in more than 20 languages)
<b>Power Supply</b>	12V/2A
<b>Power Consumption</b>	<15W (without HDD)
<b>Working Temperature</b>	-10°C - +60°C,
<b>Working Humidity</b>	10%—90%, Atm:86kpa—106kpa