



PLC-1508H1-E **08 Channel XVR**



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1508H1-E

08CH XVR



1. Features:

- ✔ Using cloud services, easily achieve a variety of network penetration; one step to achieve remote monitoring, and no need various complicated network settings. It is convenient and easy operation.
- ✔ Supports VGA, TV and HDMI output simultaneously
- ✔ Support mobile phone remote monitoring (IPhone /Android)
- ✔ Powerful Network Services (Support DHCP、PPPOE、FTP、DNS、DDNS、NTP、UPNP、EMAIL、IP Competence、IP Search 、Alarm Center) , Perfect matching (WEB、Client、SDK) , Easy to achieve mutual-communication.
- ✔ More than 20 kinds of languages supported (Arabic、Brazilian、Bulgarian、Czech、Dutch、English、Persian、Finnish 、French、German、Greek、Hebrew、Hungarian、Indonesian、Italian、Japanese、Polish、Portuguese、Romanian、Russian、Chinese Simplified、Slovak、Spanish、Swedish、Thai、Chinese Traditional、Turkish、Vietnamese) , no language restrictions.
- ✔ Free replacement for boot interface and free selection for interface style.
- ✔ Support Slice playback、 Instant playback、 Instant Recording、 Estimation、 IVS

2. Main Board configuration:

DSP	RAM	HDD
HI3520DV400	4G	1*8TB

3. Specification:

System	Video Compression	H.265
	Operating	Embedded Linux
Video	Input	8CH
	Resolution	H5M/H4M/H3M/1080N/720P
	VGA output	Yes
	CVBS output	Yes
	HDMI output	Yes
Audio	Audio input	1CH audio in
	Audio out	1CH audio out
	Intercom	Yes
Alarm	Alarm input	Optional
	Alarm	Optional
IVS	Perimeter alert	Cordon/warning area
	Object care	Object left/Object missing
Recording	Recording mode	8CH H5M 8fps
	Record mode	Schedule, Manual, Motion, External Alarm, instant recording
Playback	Simultaneous playback	8CH H5M 8fps
	Playback Model	Normal, Event, Instant playback, Slice playback
	Search mode	Time, Calendar, Event, Channel
Backup	USB HDD /U-disk	Yes
	USB DVD Burner	Yes
	Backup file format	H26X/DAV/AVI/MP4
Remote Access	Browsers	IE browsers
	CMS	Yes, supports Pollo View
	Mobile phone operating system	IPhone, Android
Storage	HDD number	1SATA, Max 8T
PTZ	Connector	1*RS485
	Protocol	PELCO,PELCO, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
	Control mode	Pan, Tilt, Zoom, Preset, Cruise, Trace
Network	Ethernet port	10 / 100 Mbps Ethernet (RJ-45)
	Network protocol	TCP/IP, DHCP, NTP, SMTP
Other	Remote control	Optional
	Power supply	12V 2A POWER
	Working temperature	-10°C ~60°C
	Humidity	10% ~ 90% Humidity
	Weight	1.25 KG