



## PLC-1508H1/PR-E 08 Channel XVR



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-1508H1/PR-E

### 08 Channel XVR



### Specifications:

<b>Model</b>	<b>PLC-1508H1/PR-E</b>
<b>Main Processor</b>	HI3520DV400
<b>Operating System</b>	Embedded LINUX
<b>Input</b>	Normal Mode: Analog: 8*(TVI/AHD: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI: 3M; AHD/TVI/CV I: 1080P/720P; Analog: 960H), Analog+Network: 2*Analog(5MP)+7*network(MAX 5MP),4*Analog(5MP)+5*network(MAX 5MP),6*Analog(5MP)+3*network(MAX 5MP), Network: 12*5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤48M)
<b>Input</b>	8CH BNC
<b>Signal Type</b>	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
<b>Output</b>	1HD,1 VGA, CVBS
<b>Input</b>	2 Channel, RCA
<b>Two-way Audio</b>	NO
<b>Output</b>	1 Channel, RCA
<b>Sensor Input</b>	4 CH
<b>Output</b>	1 CH
<b>Motion Detection</b>	8 Channel(max 12 Channel in pure network mode)
<b>Trigger Events</b>	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
<b>Email Alarm</b>	Send Image to The Designated E-mail
<b>Face Comparison</b>	1 channel video stream face Comparison(1 face databases with 10 face images)
<b>Interface</b>	RS485
<b>Protocol</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	110~921600
<b>Address</b>	0~255
<b>VGA</b>	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720 60Hz,1024 × 768/60Hz
<b>HD Output</b>	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
<b>Display Split</b>	16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
<b>Privacy Masking</b>	3 Rectangular Zones (Each camera)
<b>OSD</b>	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Video Compression</b>	H.265+/H.265/H.264+/H.264
<b>Audio Compression</b>	G.711u/G.711a

<b>Resolution</b>	5MP_Lite(1296×1944),4MP_Lite(1280×1440),3MP_Lite(1024×1536),1080N(960×1080),720P(1280×720),960H(P:960×576/N:960×480)
<b>Video Quality</b>	Worst/Worse/Ordinary/Well/Best
<b>Record Rate</b>	Analog: PAL: 5MP_Lite(1296×1944 8*6fps),4MP_Lite(1280×1440 8*8fps),3MP_Lite(1024×1536 8*10fps),1080N(960×1080 8*15fps),720P(1280×720 8*15fps), 960H(960×576 8*25fps), NTSC:5MP_Lite(1296×1944 8*6fps),4MP_Lite(1280×1440 8*8fps),3MP_Lite(1024×1536 8*10fps),1080N(960×1080 8*15fps),720P(1280×720 8*15fps), 960H(960×576 8*25fps), Pure IP(H.265):, PAL: 5MP@8×25fps,4MP@12×25fps,3MP@12×25fps,1080P@12×25fps,960P@12×25fps,720P@12×25fps,D1@12×25fps, NTSC: 5MP@8×30fps,4MP@12×30fps,3MP@12×30fps,1080P@12×30fps, 960P@12×30fps, 720P@12×30fps, D1@12×30fps
<b>Record Mode</b>	Manual\Timer\Motion Detection\AI Alarm\Alarm Input
<b>Decode Capability</b>	2CH 1080P@30fps
<b>Sync Playback</b>	Pure Analog: 8CH 960H@25fps, 8CH 720P@15fps, 7CH 1080N@15fps, 7CH 5M_LITE@6fps, 7CH 4M_LITE@8fps, 7CH 3M_LITE@10fps, Mixture mode: 4CH D1@25fps, 2CH 1080P@25fps, 1CH 5MP@25fps, Pure Network: 4CH D1@25fps, 2CH 1080P@25fps, 1CH 5MP@25fps
<b>Remote Playback</b>	4 Channel / 1Channel
<b>Search Mode</b>	ALL, Channel, Manual, Time, Date, Motion Detection
<b>Playback Functions</b>	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen
<b>Smart Phone Playback</b>	4 Channel
<b>Backup Mode</b>	USB Device(with format FAT 32 )/Network/FTP
<b>Interface</b>	1 RJ45 10M/100M Adaptive Ethernet Interface
<b>Network Functions</b>	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
<b>DDNS</b>	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
<b>Web Browser</b>	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
<b>CMS Software</b>	Support Windows 7/ Windows 8/Windows 10
<b>Extra Stream</b>	CIF/D1(1-12fps)
<b>Smart Phone</b>	iPhone, ipad, Android ,Android pad
<b>Interface Type</b>	1 SATA Interface
<b>Capacity</b>	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
<b>Language</b>	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese, Japanese
<b>UTC Control</b>	YES
<b>USB Interface</b>	2 USB 2.0 Interfaces
<b>Power consumption</b>	DC 12V/2A ≤6W (Without Hard Disk)
<b>Working Environment</b>	-10~55°C/10~90%
<b>Dimension (W×D×H)</b>	260*215*43(mm)
<b>Weight</b>	2kg (Without HDD)