



## **PLC-1516H1-E** **16 Channel XVR**



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-1516H1-E

### 16 Channel XVR



#### 1. Features:

- ✔ Using cloud services, easily achieve a variety of network penetration; one step to achieve remote monitoring, and no need various complicated network settings. It is convenient and easy operation.
- ✔ Supports VGA, TV and HDMI output simultaneously
- ✔ Support mobile phone remote monitoring (iPhone /Android)
- ✔ Powerful Network Services (Support DHCP、PPPOE、FTP、DNS、DDNS、NTP、UPNP、EMAIL、IP Competence、IP Search 、Alarm Center) , Perfect matching (WEB、Client、SDK) , Easy to achieve mutual-communication.
- ✔ More than 20 kinds of languages supported (Arabic、Brazilian、Bulgarian、Czech、Dutch、English、Persian、Finnish 、French、German、Greek、Hebrew、Hungarian、Indonesian、Italian、Japanese、Polish、Portuguese、Romanian、Russian、Chinese Simplified、Slovak、Spanish、Swedish、Thai、Chinese Traditional、Turkish、Vietnamese) , no language restrictions.
- ✔ Free replacement for boot interface and free selection for interface style.
- ✔ Support Slice playback、Instant playback、Instant Recording、Estimation、IVS

#### 2. Main Board configuration:

DSP	RAM	HDD
HI3521D	8G	1*8TB

### 3. Specification:

<b>System</b>	Video Compression	H.265
	Operating	Embedded Linux
<b>Video</b>	Input	16CH
	Resolution	H5M/H4M/H3M/1080N/720P
	VGA output	Yes
	CVBS output	Yes
	HDMI output	Yes
<b>Audio</b>	Audio input	1CH audio in
	Audio out	1CH audio out
	Intercom	Yes
<b>Alarm</b>	Alarm input	Optional
	Alarm	Optional
<b>IVS</b>	Perimeter alert	Cordon/warning area
	Object care	Object left/Object missing
<b>Recording</b>	Recording mode	16CH H5M 6fps Rec
	Record mode	Schedule, Manual, Motion, External Alarm, instant recording
<b>Playback</b>	Simultaneous playback	16CH H5M 6fps
	Playback Model	Normal, Event, Instant playback, Slice playback
	Search mode	Time, Calendar, Event, Channel
<b>Backup</b>	USB HDD /U-disk	Yes
	USB DVD Burner	Yes
	Backup file format	H26X/DAV/AVI/MP4
<b>Remote Access</b>	Browsers	IE browsers
	CMS	Yes, supports Pollo View
	Mobile phone operating system	IPhone, Android
<b>Storage</b>	HDD number	1SATA, Max 8T
<b>PTZ</b>	Connector	1*RS485
	Protocol	PELCO, PELCOD, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
	Control mode	Pan, Tilt, Zoom, Preset, Cruise, Trace
<b>Network</b>	Ethernet port	10 / 100 Mbps Ethernet (RJ-45)
	Network protocol	TCP/IP, DHCP, NTP, SMTP
<b>Other</b>	Remote control	Optional
	Power supply	12V 2A POWER
	Working temperature	-10°C ~60°C
	Humidity	10% ~ 90% Humidity
	Weight	1.25 KG