



**PLC-1532H8/PR**  
32 Channel XVR



**Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-1532H8/PR

### 32 Channel XVR



### Specifications:

<b>Model</b>	PLC-1532H8/PR
<b>Operating System</b>	Embedded LINUX
<b>Input</b>	Analog: 32*1080P Analog + Network: 30*Analog(1080P)+2*network(Max 8MP), 28*Analog(1080P)+4*network(Max 8MP), 26*Analog(1080P)+6*network(Max 8MP), 24*Analog(1080P)+8*network(Max 8MP), 22*Analog(1080P)+10*network(Max 8MP), 20*Analog(1080P)+12*network(Max 8MP), 18*Analog(1080P)+14*network(Max 8MP), 16*Analog(1080P)+16*network(Max 8MP), 14*Analog(1080P)+18*network(Max 8MP), 12*Analog(1080P)+20*network(Max 8MP), 10*Analog(1080P)+22*network(Max 8MP), 8*Analog(1080P)+24*network(Max 8MP), 6*Analog(1080P)+26*network(Max 8MP), 4*Analog(1080P)+28*network(Max 8MP), 2*Analog(1080P)+30*network(Max 8MP) Network: 32*network(Max 8MP)(Total incoming bandwidth ≤160M)
<b>Input</b>	32CH BNC
<b>Signal Type</b>	Analog/AHD/CVI/TVI 2.0/Network
<b>Output</b>	1HD, 1 VGA, 1CVBS
<b>Input</b>	12 Channel, RCA
<b>Output</b>	1 Channel, RCA
<b>Sensor Input</b>	16 Channel
<b>Output</b>	4 Channel
<b>Motion Detection</b>	32 Channel
<b>Trigger Events</b>	Recording, Email, Screen tips, Buzzer, Push notifications (motion detection)
<b>Email Alarm</b>	Send Image to The Designated E-mail
<b>Interface</b>	RS485
<b>Protocol</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	110~921600
<b>Address</b>	0~255
<b>VGA</b>	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
<b>HD Output</b>	Resolution: 3840×2160/30Hz, 2560x1440/30Hz, 1920 × 1080P /60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
<b>Display Split</b>	32 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
<b>Privacy Masking</b>	3 Rectangular Zones (Each camera)
<b>OSD</b>	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Video Compression</b>	H.265/H.265+/H.264+/H.264

<b>Audio Compression</b>	G.711u
<b>Resolution</b>	Half 1080P(960×1080);720P(1280×720);960H(P:960×576/N:960×480)
<b>Video Quality</b>	worst/worse/ordinary/well/best
<b>Record Rate</b>	Analog: PAL:Half 1080P(960x1080 32*15fps),720P(1280×720 32*15fps), 960H(960×576 32*22fps) NTSC:Half 1080P(960x1080 32*15fps),720P(1280×720 32*15fps), 960H(960×480 32*22fps) Pure IP(H.265): PAL:8MP@17×25fps,5MP@26×25fps,4MP@32×25fps,3MP@32×25fps,1080P@32×25fps,960P@32×25fps,720P@32×25fps,D1@32×25fps NTSC: 8MP@17×30fps,5MP@26×30fps,4MP@32×30fps,3MP@32×30fps,1080P@32×30fps,960P@32×30fps, 720P@32×30fps, D1@32×30fps
<b>Record Mode</b>	Manual\Timer\Motion Detection\alarm
<b>Decode Capability</b>	9CH 1080P@30fps
<b>Sync Playback</b>	Pure Analog: 32CH 1080N@15fps Mixture Mode: 1CH 8MP@30fps, 1CH 5MP@30fps, 2CH 4MP@30fps, 3CH 3MP@30fps, 4CH 1080P@30fps, 4CH 1080N@12fps Pure Network: 2CH 8MP@30fps, 3CH 5MP@30fps, 4CH 4MP@30fps, 5CH 3MP@30fps, 9CH 1080P@30fps
<b>Remote Playback</b>	4 Channel / 1Channel
<b>Search Mode</b>	ALL, Channel, Manual, Time, Date, Motion Detection
<b>Playback Functions</b>	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
<b>Smart Phone Playback</b>	4 Channel
<b>Backup Mode</b>	USB Device(with format FAT 32 )/Network/FTP
<b>Interface</b>	1 RJ45 10M/100M/1000M Adaptive Ethernet Interface
<b>Network Functions</b>	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
<b>DDNS</b>	Dyndns, change ip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
<b>Web Browser</b>	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
<b>CMS Software</b>	Support Windows XP /Windows Vista/Windows 7/Windows 8
<b>Extra Stream</b>	CIF/D1(1-22fps)
<b>Smart Phone</b>	iPhone, ipad, Android ,Android pad
<b>Interface Type</b>	8 SATA Interface
<b>Capacity</b>	8 SATA Hard Disk (3.5" SATA, Up to 64TB) + 1 E-SATA Interface (Up to 8TB)
<b>Language</b>	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
<b>UTC Control</b>	YES
<b>USB Interface</b>	2 USB 2.0 Interfaces
<b>Power consumption</b>	AC 115~230v ≤35W (Without HDD)
<b>Working Environment</b>	-10~55°C/10~90%
<b>Dimension (W×D×H)</b>	440*450*95(mm)
<b>Weight</b>	9.8kg (Without HDD)

**Dimensions:**

