



PLC-322M-IR3

Bullet 2 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-322M-IR3

Bullet 2 MP



1. Specifications:

Image Sensor	1/2.9" 2.0 MP HD Color Image Sensor CMOS
Signal System	PAL/NTSC
Horizontal Resolution	2.0 MP (1920 H x 1080 V)
Lens	3.6 mm
IR Range	Up to 30 m IR
Min. Illumination	Color (0.1 Lux), White and Black (0.01 Lux IR LED on)
Electronic Shutter	1/50 s (1/60 s) - 1/100,000 s (Auto/Fixed)
Video Output	TVI/AHD/CVI/CVBS Optional, Default Setting: TVI
Exposure	Auto
Auto-gain	Yes
White Balance	Auto
BLC	Auto
AGC	Yes
Noise Reduction	3 DNR
UTC	Yes
DWDR	Yes
Dimensions	139 mm * 63 mm * 63 mm
S/N Ratio	≥40 dB
Video Output	1.0 VP - P Composite Output (75Ω / BNC)
Frame Rate	30 fps (60Hz), 25 fps (50Hz)
D&N	Supports ICR
Power Consumption	0.4W (2.5 W After IR LED is Powered on)
Power Supply	DC 12 V (+/-10%)
Ingress Protection	IP66
Working Temperature	-20°C - 50°C, 10% - 90% (humidity)
Working Humidity	≤95% RH, No Dew

2. Dimensions:

