



PLC-322P-WR3
Warm Light Bullet 2MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-322P-WR3/PR

Warm Light Bullet 2MP



Main Features:

- ❖ 2MP HD Analog Output (AHD/TVI/CVI).
- ❖ 1/2.9" High-Performance Progressive Scan COMS
- ❖ No Delay, Lossless, Long Distance transmission Up to 400 meters
- ❖ Support 3.6mm Lens
- ❖ Support DNR /DWDR
- ❖ Support low illumination, warm light day night full color
- ❖ Support ICR switch, realize day & night monitor
- ❖ Support OSD Menu/DIP Switch /circulation button switch(Optional)
- ❖ Applicable to the Financial Departments, Telecommunications, Government, schools, airports, factory, Hotels , Museum, Public transportation and Other place

Specifications:

Parameter Classification	Parameter Name	Parameter Value
Camera	Image Sensor	1/2.9" 2MP Progressive Scan COMS
	Resolution	1920*1080
	Image System	PAL/NTSC
	Light ON	0.1 lux @ (F2.0, AGC ON)
	Electronic shutter	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
	Lens	3.6mm
	LEDs	2 PCS 3500K soft warm light
	SNR	>52dB (AGC off)
	Full color distance	30m
	Video Frame Rate	1080P@25fps, 1080P@30fps
	Video Output	TVI/AHD/CVI/CVBS
Menu	D&N	Support ICR EXT/Auto / Color/ BW
	DNR	Support 2D 3D NR
	WDR	DWDR
	Smart LED	Support Auto/Manual Model
	White Balance	ATW / MWB
	BLC	Support
	Image set	contrast、sharpness、saturate、3DNR、2DNR、DWDR
	Language	English, Chinese
General	Power Supply	12VDC ± 10 %;
	Operating Conditions	(-20° C to 50° C), Humidity 90% or less (non-condensing)
	Protection level	IP66
	Power Consumption	Max. 3W (Max. 3W with LED ON)
	Dimensions	154mm*71mm*71mm

Dimensions:

