



PLC-4212M-IR6/PR

Bullet 12 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-4212M-IR6/PR

Bullet 12 MP



Specifications:

Model No.	PLC-4212M-IR6/PR
Image Sensor	1/1.7" SONY Low Illumination CMOS Sensor
Resolution	12 MP (4000 * 3000)
Effective Pixels	4072 (H) × 3046 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25 - 1/10000 s; NTSC 1/25 - 1/10000 s
Min. Illumination	0.01 Lux
S/N Ratio	≥52 dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Focal Length	3.6 mm - 11 mm
Focus Control	Auto
Lens Type	Motorized
Pixels	12 MP
Infrared LED	42 μ x 6 pcs
Infrared Distance	60 m
IR Status	Auto-control
IR Power On	Auto-control
Ethernet	RJ-45 (10/100 Base - T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Supports ONVIF 2.4
P2P	Yes, Supports QR Code
PoE	Internal, Supports IEEE 802.3af
Video Delay	0.3 s (Within the Lane)
Main Stream 1	4000 * 3000 @ 20 fps 3840 * 2160 @ 30 fps 3072 * 2048 @ 30 fps
Main Stream 2	2592 * 1944 @ 30 fps 2560 * 1920 @ 30 fps
Main Stream 3	2560 * 1440 @ 30 fps 1920 * 1080 @ 30 fps

	1280 * 720 @ 30 fps
Sub-stream 1	720 * 480 @ 20 fps 720 * 480 @ 30 fps
IE Brower	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53), Mac Safari (Lower Than Version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
Day/Night	Color/ B & W (IR-CUT)
Image Configuration	Saturation/Brightness/Contrast /Sharpness, Mirror, 3DNR, White Balance, FLK (Flicker Control), Video Tampering
Corridor Pattern	Yes
Defog Mode	Yes
ROI	Yes
BLC	Yes
WDR	DWDR: 50 dB
Motion Detection	Yes
Privacy Masking	3 Rectangular Zones
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Dutch
Audio	2-Way Audio
Alarm	1 Channel Input/output
SD Card Slot	Yes, Supports Max. 128 GB
Housing	Metal, IP67
Anti-cut Bracket	Optional
IR Cut Filter	Yes
Operation Temperature	-20 °C - +60 °C RH 95% Max.
Ingress Protection	IP66
Power Source	DC 12 V ± 10%, 1100 mA
Dimension	179 (W) x 90 (H) x 90 (D) mm
Weight	1400 g

Dimensions:

