



PLC-422M-AI-IR3/PR
Bullet 2 MP Smart AI



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-422M-AI-IR3/PR

Bullet 2 MP Smart AI Camera



Specifications:

Model No.	PLC-422M-AI-IR3/PR
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2 MP 1080p
Effective Pixels	1945 (H) * 1097 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25 s - 1/10000 s; NTSC 1/25 s - 1/10000 s
Minimum Illumination	0.002 Lux
S/N Ratio	≥52 dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Focal Length	3.6 mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	3 MP
Infrared LED	14 μ x 20 pcs
Infrared Distance	25 m
IR Status	Auto-control
IR Power On	Auto-control
Ethernet	RJ-45 (10/100 Base - T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Supports ONVIF 2.4
P2P	Yes, Supports QR Code
PoE	Internal, Supports IEEE 802.3af
Video Delay	0.3 s (Within the Lane)
Main Stream 1	2304 * 1296 @ 20 fps
Main Stream 2	1920 * 1080 @ 30 fps
Main Stream 3	1280 * 720 @ 30 fps
Sub-stream 1	720 * 480 @ 20 fps 720 * 480 @ 30 fps

Tri-stream	352 * 288 @ 20 fps 352 * 288 @ 30 fps
IE Brower	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53), Mac Safari (Lower Than Version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
Intelligent Analysis	Intrusion Detection, Line Cross Detection, Loiter Detection, People Gather Detection
Recognition	Face Detection and Recognition (Max. Support: 2000 Faces)
Day/Night	Color: B&W (IR-CUT)
Image Configuration	Saturation/Brightness/Contrast /Sharpness, Mirror, 3DNR, White Balance, FLK (Flicker Control), Video Tampering, ROI
Defog Mode	Yes
ROI	Yes
BLC	Yes
WDR	WDR: 96 dB
Motion Detection	Yes
Privacy Masking	3 Rectangular Zones
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Dutch, Czech, Vietnamese
Audio	Optional
SD Card Slot	Optional, Supports Max. 512 GB
Housing	Metal, IP67
Anti-cut Bracket	Yes
IR Cut Filter	Yes
Operation Temperature	-20°C - +60°C RH 95% Max.
Storage Temperature	-20°C - +60°C RH 95% Max.
Power Source	DC 12 V ± 10%, 900 mA
Dimensions	186 mm (W) x 75 mm (H) x 71 mm (D)
Weight	500 g

Dimensions:

