



PLC-425M-IR3

Bullet 5 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-425M-IR3

Bullet 5 MP



1. Features:

- ✔ The device uses a high-performance processor with a 5.0-megapixel CMOS imaging sensor.
- ✔ Device uses Linux embedded OS and consumes less power.
- ✔ Device uses H.265 encoding, high compression ratio and lower stream.
- ✔ Device supports ICR automatic switchover and achieves round-the-clock monitoring.
- ✔ Device supports network interruption, IP conflict, motion detection and video blind smart alarm.
- ✔ Device supports abnormal automatic recovery and auto-reconnect functionality.
- ✔ Device supports watermark encryption and prevents data from being tampered.
- ✔ Device supports DC 12 V/PoE (choice) and is easy to install.
- ✔ Device also supports IP66 waterproofing grade.
- ✔ Device also provides SDK development kit and access to other video management platforms.

2. Specifications:

Camera	Image Sensor	1/2.5" CMOS Sensor
	Max Resolution	2560 * 1920
	Minimum Illumination	Color 0.1 Lux @ F 1.2, Black/White 0.01 Lux @ F 1.2;
	Electronic Shutter	1/25 s - 1/100000 s, Manual/Automatic Adjustment
	Day and Night	Color/Black and White/Automatic, IR-CUT Automatic Switching
	Infrared Distance	30 m
	WDR	Yes
	SNR	≥50 dB
	Gain Control	Automatic
	White Balance	Automatic
Lens Parameter	Type	Fixed Focal Lens
	Focal Length	3.6 mm
	Interface	M 12
Video Parameter	Video Compression	H.265/H.264
	Bit Rate	32 kbps – 8192 kbps, Adjustable, Supports VBR/CBR
	Frame	PAL: Main Stream (2560 * 1920 @ 15 fps), Sub-stream (D1 @ 25 fps) NTSC: Main Stream (2560 * 1920 @ 15fps), Sub-stream (D1 @ 30 fps)
Function	OSD Superimpose	Time, Channel name, Position, Picture
	Image Settings	Brightness, Contrast, Sharpness, Saturation
	Record Mode	Manual, Detection, Timing Video, Alarm
	Storage	N/A
	Defaults	Supports Key to Restore Defaults
	Browser	Supports Above IE6
	User Management	Supports Multi-level User Administration
	Alarm and Data Transmission	Supports FTP, E-mail Browser, VMS
	Privacy Shelter	Yes
	Motion Detect	Yes
Interface	Network Interface	1 RJ45 10/100 M Ethernet Interface
	Protocol	Supports TCP/IP/HTTP/RTSP/FTP/PPPOE/RTCP/SMTP/DHCP/DDNS/NTP/UPnP/ SNMP
	Access Protocol	Supports Standard ONVIF
	Smartphone Platform	Supports iPhone, iPad, Android
Others	Ingress Protection	IP66
	Shell Material	Metal
	Power Supply	DC 12 V/PoE
	Power Consumption	10 W Max
	Work Environment	-20°C - +55°C, Operating Humidity: ≤95%
	Install	Scaffolding; Ceiling-mounted