



**PLC-432P-IR2/PR**  
Dome 2MP



**Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-432P-IR2/PR

### Dome 2MP



### Specifications:

<b>Model NO.</b>	<b>PLC-432P-IR2/PR</b>
<b>Image Sensor</b>	1/2.9" Full HD CMOS Sensor
<b>Resolution</b>	2MP 1080P
<b>Effective Pixels</b>	1920(H)*1080(V)
<b>Compression</b>	H.264/H.265/JPEG/AVI /MJPEG
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter Time</b>	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
<b>Minimum Illumination</b>	0.01Lux
<b>S/N Ratio</b>	≥52dB
<b>Scanning System</b>	Progressive
<b>Video Output</b>	Network
<b>Reset Button</b>	Optional
<b>Focus Length</b>	2.8mm
<b>Focus Control</b>	Fixed
<b>Lens Type</b>	Fixed
<b>Pixels</b>	3MP
<b>Infrared LED</b>	14μ x 18PCS
<b>Infrared Distance</b>	20M
<b>IR Status</b>	Auto Control
<b>IR Power On</b>	Auto Control
<b>Ethernet</b>	RJ-45 (10/100Base-T)
<b>Protocol</b>	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
<b>ONVIF</b>	Support ONVIF 2.4
<b>P2P</b>	YES, Support QR Code
<b>POE</b>	Optional, Support IEEE 802.3af
<b>Video Delay</b>	0.3S (Within the Lane)
<b>Main Stream 1</b>	2304*1296@20fps
<b>Main Stream 2</b>	1920*1080@25fps
<b>Main Stream 3</b>	1280*720@30fps
<b>Sub Stream 1</b>	720*480@20fps 720*480@30fps

<b>IE Brower</b>	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad
<b>Day/Night</b>	Color/ B&W (IR-CUT )
<b>Image Config</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
<b>Corridor Pattern</b>	Support
<b>Defog Mode</b>	Support
<b>ROI</b>	Support
<b>BLC</b>	Support
<b>WDR</b>	DWDR: 50dB
<b>Motion Detection</b>	Support
<b>Privacy Masking</b>	3 Rectangular Zone
<b>Recording Mode</b>	NVR/CMS/Web
<b>Language</b>	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederland, Czech, Vietnamese
<b>Audio</b>	Optional
<b>SD Card Slot</b>	Optional, Support Max 512GB
<b>Housing</b>	Plastic
<b>Anti-cut Bracket</b>	Optional Wall Bracket
<b>IR Cut Filter</b>	YES
<b>Operation Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 750mA
<b>Dimension</b>	99(W) x 81(H) x 80(D)mm
<b>Weight</b>	300g

### Dimensions:

