



PLC-482M-IR2/PR

Fisheye 2 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-482M-IR2/PR

Fisheye 2 MP



Specifications:

Model No.	PLC-482M-IR2/PR
Image Sensor	1/3" Aptina HD CMOS Sensor
Resolution	2 MP
Effective Pixels	2304 (H) x 1536 (V)
Compression	H.264/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25 - 1/10000 s, NTSC 1/25 - 1/10000 s
S/N Ratio	≥52 dB
Scanning System	Progressive
Video Output	Network, CVBS
Reset Button	Yes
Focal Length	Board Lens 1.05 mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	5 MP
Infrared LED	42 μ x 3 pcs
Infrared Distance	20 m
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto-control
Ethernet	RJ-45 (10/100 Base - T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Supports ONVIF 2.4
P2P	Yes, Supports QR Code
PoE	Internal PoE, Supports IEEE 802.3af
Video Delay	0.3 s (Within the Lane)
Main Stream 1	1520 * 1520 @ 25 fps
Main Stream 2	1024 * 1024 @ 25 fps
Sub-stream 1	720 * 720 @ 25 fps
Tri-stream	512 * 512 @ 25 fps
IE Brower	IE9 - 11, Google Chrome (Under Ver. 45), Firefox (Under Ver. 53), Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

Antenna	3 dB
Hotspot	Yes
Wi-Fi	Wi-Fi (IEEE 802.11 b/g/n), 2.4 Ghz
Wi-Fi Range	No Obstacles 300 m Max.
Day/Night	Color/B&W (IR-CUT)
Image Configuration	Saturation/Brightness/Contrast /Sharpness, Mirror, White Balance, FLK (Flicker Control)
WDR	DWDR: 50 dB
Motion Detection	Yes
Privacy Masking	3 Rectangular Zones
Recording Mode	NVR/VMS/Web/SD Card
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Dutch, Czech
Audio	2-way Audio (3.5 mm Audio Interface)
Alarm	1 Channel Input/Output
SD Card Slot	Supports 128 GB MicroSD with External SD Card Slot
Housing	Body: Metal. Bracket: Plastic
Anti-cut Bracket	No
IR Cut Filter	Yes
Operation Temperature	-20 °C - + 60 °C RH 95 % Max.
Storage Temperature	-20 °C - +60 °C RH 95 % Max.
Power Source	DC 12 V ± 10 %, 950 mA
Dimension	∅ 120 x 49 (H) mm
Weight	500 g

Dimensions:
