




PLC-51232H2/PR

12 MP 32 Channel NVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-51232H2/PR

12 MP 32 Channel NVR



Specifications:

Model No.	PLC-51232H2/PR
Main Processor	ARM Cortex A17 Quad-core Processor
Operating System	Embedded Linux
Input	32 Channel (4000 × 3000, 4096 × 2160, 2592 × 1944, 2048 × 1536, 1920 × 1080, 1280 × 960, 1280 × 720, etc)
Output	1 VGA, 1 HD
Input	1 Port RCA
Output	1 Port RCA (Linear, 1kΩ)
Audio Bit Rate	64 kbps
Audio Compression Standard	G.711
Sensor Input	No
Output	No
Motion Detection	32 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, Alarm Output
HD Output 1	4K (3840 × 2160)/60 Hz, 4K (3840 × 2160)/30 Hz, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA	1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Display Split	32 Channel x D1/25 Channel x D1/16 Channel x D1/9 Channel x D1/4 Channel x D1/1Channel x 1080p/1 Channel x 3 MP/1 Channel x 4 MP/1 Channel x 5 MP/1 Channel x 4K/1 Channel x 12 MP
Digital Zoom	Yes
OSD	Camera Title, Time, Recording, Motion Detection
Video Compression	H265/H264/H265+/H264+
Resolution	12 MP (4000 × 3000), 4K (4096 × 2160), 5 MP(2592 × 1944), 4 MP (2688 × 1520), 3 MP (2048 × 1536), 1080p (1920 × 1080), 960p (1280 × 960), 720p (1280 × 720), D1 (720 × 576/720 × 480)
Record Rate	PAL: 12 MP @ 25 × 25 fps, 4K @ 30 × 25 fps, 5 MP @ 36 × 25 fps, 4 MP @ 36 × 25 fps, 3 MP @ 36 × 25 fps, 1080p @ 36 × 25 fps, 960p @ 36 × 25 fps, 720p @ 36 × 25 fps, D1 @ 36 × 25 fp NTSC: 12 MP @ 25 × 30 fps, 4K @ 30 × 30 fps, 5 MP @ 32 × 30 fps, 4 MP @ 32 × 30 fps, 3 MP @ 32 × 30 fps, 1080p @ 32 × 30 fps, 960p @ 32 × 30 fps, 720p @ 32 × 30 fps, D1 @ 32 × 30 fps

Record Mode	Manual/Timer/Motion Detection
Local Sync Playback	3 Channel 12 MP @ 15 fps, 4 Channel 4K @ 30 fps, 6 Channel 5 MP @ 30 fps, 8 Channel 4 MP @ 30 fps, 10 Channel 3 MP @ 30 fps, 16 Channel 1080p @ 30 fps, 16 Channel 960p @ 30 fps, 16 Channel 720p @ 30 fps
Decode Capability	4 Channel 4K (3840 × 2160) @ 30 fps
Remote Sync Playback	Yes
Search Mode	All, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast Play, Digital Zoom
Backup Mode	USB Device/Network
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Incoming Bandwidth	300 Mbps
Network Functions	TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, PoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P
Onvif Version	Supports Onvif 2.4
Web Browser	IE8 - 11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53)
CMS Software	Supports Windows 7/Windows 8/Windows 10
Cloud Support (P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
Interface Type	2 SATA Interface
Storage Capacity	Up to 12 TB capacity
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farsi, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
USB Interface	1 USB 2.0 Interfaces, 1 USB 3.0 Interface
Power Supply	DC 12 V/4A
Working Environment	-10°C - 55°C/10 - 90%
Dimension (W × D × H)	310 * 295 * 46 (mm)
Weight	3.5 kg (Without HDD)

Dimensions:

