



PLC-9236-IR25/PR
36X Speed Dome 2 MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-9236-IR25/PR

36X Speed Dome 2 MP



Specifications:

Model	PLC-9236-IR20/PR
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	2 MP
Compression	H.265/H.264
S/N Ratio	>50 dB
Horizontal Rotation Speed	200°/s
Horizontal Rotation Range	0° - 360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	0° - 90°
Preset Points	220
Guard Tours	3 Groups
Guard Points	Max.16 Points
Focal Length	4.6 mm - 165 mm
Focus Control	36X Optical Zoom
Infrared LED	∅ 42 x 8 pcs IR LEDS + 4 pcs LED Laser
IR Range	250 m
Day-night Mode	Auto
Network Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
ONVIF	Yes
Network Interface	Built-in RJ45 Network Interface, Supports 10M/100M IP DATA
Stream Type	Main Stream/Sub-stream/MJPEG
Audio	Optional
Alarm	Optional
Ingress Protection	IP67
Operating Temperature	Indoor: 0° - +40°, Outdoor: -40° - +60°
Operating Humidity	≤90% Non-condensing
Power	DC 12 V/4 A
Lightning Protection	Transient Voltage 6000 V
Dimension	33 x 33 x 52 (cm)
Weight	13.7 kg

Dimensions:

