



PLC-9236-IR25/PR
36x Speed Dome 2MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-9236-IR25/PR

36x Speed Dome 2MP



Specifications:

Model	PLC-9236-IR25/PR
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	2MP
Compression	H.265/H.264
S/N Ratio	>50db
Horizontal Rotation Speed	200°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	0°~90°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Focus Length	4.6mm-165mm
Focus Control	36X Optical Zoom
Infrared LED	∅ 42 x 8PCS IR LEDS + 4PCS LED Laser
IR Range	250m
Day-night mode	AUTO
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Stream type	Main Stream / Sub Stream / MJPEG
Audio	Optional
Alarm	Optional
Weatherproof	IP67
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Noncondensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	33x33x52(cm)
Weight	13.7Kgs

Dimensions:

