



PLC-9520-IR25/PR
20x Speed Dome 5MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-9520-IR25/PR
20x Speed Dome 5MP

Specifications:

Model	PLC-9520-IR25/PR
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	5MP
Compression	H.265/H.264
S/N Ratio	>50db
Horizontal Rotation Speed	120°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Focus Length	4.7mm-94mm
Focus Control	20X Optical Zoom
Infrared LED	∅ 42x8PCS IR LEDS + 2PCS Laser LED
IR Range	250m
Day-night mode	AUTO
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Stream type	Main Stream / Sub Stream / MJPEG
Audio	Optional
Alarm	Optional
Weatherproof	IP67
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non-Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	31x31x44(cm)
Weight	10.7Kgs

Dimensions:

