



PLG-5219

Tripod Turnstile



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au








PLG-5219



Tripod Turnstile

1. Features

-  Motor options are available with or without brush.
-  The gate comes with a compact size that is suitable to small size applications.
-  This gate is mainly used for commercial office buildings, libraries, residential areas, construction sites, industrial plants, marquee golf tournaments, state fairs, special sporting events and festivals etc.
-  The device has a special lock to prevent from tampering.
-  The gate comes with both semi-automatic and fully automatic options.

2. Specifications:

Model	PLG-5219 (Automatic Tripod Turnstile)
Body Material	Stainless Steel Material
Working Voltage	AC 220 V ± 10 V, 50Hz or AC 110 V/60 Hz
Control Type	IC/ID/Barcode Control
Rated Power	80 W
Working Mode	Unidirectional or Bidirectional
Working Temperature	-30°C - +70°C
Operating Humidity	≤90% Non-condensing
Operation Life	≥5 Million Times
Passing Speed	40 - 50 Persons/Minute
Open Style	Retractable
Relative Humidity	≤95%, Non-condensing
Size	1200 * 1000 * 300 mm
Weight	55.00 kg
Tripod Arm Length	≤ 500 mm
Material	SUS (304#), Thickness ≥ 1.5 mm
Mechanism	DC 24 V Solenoid Lock
MCBF	3,000,000 Cycles
Communication Interface	TCP/IP
Reading Cards	IC/ID
Operating Time	1 s
Protection Grade	IP54
Operating Places	Government Agencies, Residential Areas, Schools etc.