



PLG-T660 (6s) Boom Barrier Gate



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLG-T660 (6s)

Boom Barrier Gate



1. Features

- ❖ The barrier gate will automatically close if it hits an obstacle during closing.
- ❖ The device has a powerful AC motor that virtually requires no maintenance.
- ❖ You can choose the barrier beam/arm to be from 3 meters to 6 meters. Moreover, you can also select the closing time from 1 second to 6 seconds.
- ❖ The barrier gate can be both right-installed and left-installed.
- ❖ All the operation process is soft without any noise and shaking.
- ❖ The gate has infrared photocell interface, loop detector interface and IC system.
- ❖ Interface is reserved for other functions.
- ❖ Green light and red light are used inside to indicate the position of the beam.

2. Specifications:

Model	PLG-T660 (6s) Boom Barrier Gate
Overall Dimension	350L * 300W * 1050H (mm)
Net Weight	65 kg
Housing Color	Yellow/Blue
Motor Power	100 W
Noises	≤60 dB
Motor Speed	30r/min.
MCBF	5,000,000 Times
Remote Control Distance	≤30 m
Remote Controller	2 pcs
Rail Length	≤6 m (Straight Boom)
Rail Material	Aluminum Alloy
Open/Close Speed	6 s
Working Voltage	AC 110 V, 220 V – 240 V, 50 - 60 Hz
Working Temperature	-40°C - +75°C
Working Environments	Indoor, Outdoor