



## PLC-325P-IR2/PR

Bullet 5 MP



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-325P-IR2/PR

### Bullet 5 MP



### Specifications:

<b>Model No.</b>	<b>PLC-325P-IR2/PR</b>
<b>Video Output Mode</b>	AHD/TVI: 5 MP @ 20fps/12.5 fps, 4 MP @ 30 fps/15 fps, 2 MP @ 30 fps/25 fps; CVI: 4 MP @ 30 fps/25 fps, 2 MP @ 30 fps/25 fps
<b>Image Sensor</b>	1/2.5" CMOS Sensor
<b>Image Resolution</b>	5 MP: 2592 * 1944, 4 MP: 2560 * 1440, 2 MP: 1920 * 1080
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter</b>	AUTO
<b>Scanning System</b>	Progressive Scan
<b>Focal Length</b>	3.6 mm
<b>Focus Control</b>	Fixed
<b>Lens Type</b>	Fixed
<b>IR Cut Filter</b>	Yes
<b>Infrared LED</b>	14 $\mu$ x 18 pcs
<b>Infrared Distance</b>	20 m
<b>IR Status</b>	AGC Auto-control
<b>Day/Night</b>	Yes
<b>OSD Menu</b>	Yes
<b>WDR</b>	DWDR
<b>Ingress Protection</b>	IP66
<b>Noise Reduction</b>	DNR
<b>White Balance</b>	AUTO/MANUAL
<b>Gain Control</b>	AUTO
<b>Housing</b>	Plastic
<b>Bracket</b>	Yes
<b>Operation Temperature</b>	-10 °C - +60 °C RH 95% Max.
<b>Storage Temperature</b>	-20 °C - +60 °C RH 95% Max.
<b>Power Source</b>	DC 12 V $\pm$ 10%, 550 mA
<b>Dimension</b>	160.8 (W) x 62 (H) x 62 (D) mm
<b>Weight</b>	380 g

**Dimensions:**

