



PLC-5508H1/PR

5 MP 08 Channel NVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-5508H1/PR

5 MP 08 Channel NVR



Specifications:

Model No.	PLC-5508H1/PR
Main Processor	ARM Cortex A7 Processor
Operating System	Embedded Linux
Input	8 Channel (2592 x 1944, 2048 x 1536, 1920 x 1080, 1280 x 960, 1280 x 720, etc)
Output	1 VGA, 1 HD
Output	1 Port RCA (Linear, 1 kΩ)
Audio Bit Rate	64 kbps
Audio Compression Standard	G711u, G711a, ADPCM_DVI4
Motion Detection	8 Channel, MD Zones: 396 (22 x 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, Alarm Output
HD Output 1	Resolution: 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz
VGA	Resolution: 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz
Display Split	8Channel x D1/8 Channel x D1/4 Channel x D1/1 Channel x 1080P/1 Channel x 3 MP/1 Channel x 4 MP/1 Channel x 5 MP
Digital Zoom	Yes
OSD	Camera Title, Time, Recording, Motion Detection
Video Compression	H265/H264/H265+/H264+
Resolution	5 MP (2592 x 1944), 4 MP (2688 x 1520), 3 MP (2048 x 1536), 1080p (1920 x 1080), 960p (1280 x 960), 720p (1280 x 720), D1 (720 x 576/720 x 480)
Record Rate	PAL: 5 MP @ 8 x 25 fps, 4 MP @ 8 x 25 fps, 3 MP @ 8 x 25 fps, 1080P @ 8 x 25fps, 960p @ 8 x 25 fps, 720P @ 8 x 25 fps, D1 @ 8 x 25fps NTSC: 5 MP @ 8 x 30 fps, 4 MP @ 8 x 30 fps, 3 MP @ 8 x 30 fps, 1080p @ 8 x 30fps, 960p @ 8 x 30 fps, 720p @ 8 x 30 fps, D1 @ 8 x 30 fps
Record Mode	Manual/Timer/Motion Detection
Local Sync Playback	1 Channel 5 MP @ 30 fps, 1 Channel 4 MP @ 30 fps, 2 Channel 3 MP @ 30 fps, 4 Channel 1080p @ 20 fps, 4 Channel 960p @ 30 fps, 4 Channel 720p @ 30 fps
Decode Capability	4 Channel 1080p @ 20 fps
Remote Sync Playback	Yes
Search Mode	All, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast Play, Digital Zoom
Backup Mode	USB Device/Network
Interface	1 x RJ45 10M/100M Adaptive Ethernet Interface

Incoming Bandwidth	60 Mbps
Network Functions	TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, PoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P
Onvif Version	Supports Onvif 2.4
Web Browser	IE8 - 11, Google Chrome (Lower Than Ver44.), Firefox (Lower Than Ver53.)
CMS Software	Supports Windows 7/ Windows 8/Windows 10
Cloud Support (P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
Interface Type	1 SATA Interface
Storage Capacity	Up to 6 TB Capacity
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farsi German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC 52 V/2500 mA, ≤6W (Without Hard Disk and PoE)
Working Environment	-10°C - 55°C/10 - 90%
Dimension (W × D × H)	260 * 215 * 43 (mm)
Weight	2.0 kg (Without HDD)

Dimensions:

