



PLC-1504H1/PR-E

04 Channel DVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1504H1/PR-E

04 Channel DVR



Specifications:

Model	PLC-1504H1/PR-E
Inputs	4Mbps ~20Mbps IP Bandwidth defaultt is 4Mbps, decrease one Analog channel can increase 4Mbps (default decoding performance 1080P 60fps)
Bandwidth out	32Mbps
Analog video-input	4CH inputs
IP Video Input	1ch, (only IP up to 5ch)
Composite Video Input	up to 5 Ch (Analog video + IP video)
Installation wizard	Yes
Compression	Audio: G.711a Video: H.264/H.265
Display resolution	Analog :5MP-Lite:20fps 4MP-Lite:30 fps 1080P/720P/960H:30fps IP:1080P/720P Single IP channel preview up to 2MP 30 fps multi-channel preview only sub stream
Speed	Analog: 5MP-Lite:20fps (each Ch) 4MP-Lite:30fps (each Ch) 1080P/720P:PAL:25fps (each Ch)/NTSC:30fps (each Ch) IP: PAL:25fps (each Ch)/NTSC: 30fps (each Ch) Sub-stream Max PAL : 704*576:10fps (each Ch)/NTSC : 704*480:10fps (each Ch)
Event	MD (Sensitivity Level 1~8), Video loss Email, Push notification to Mobile APP
Playback Function	Fast forward / backward (2x, 4x, 8x,16x), Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite:80fps 4MPlite: 120fps 1080P: 120fps 720P:120fps
UI/Monitoring Local	UI5.0
UI/Monitoring WEB	N/A
Mobile viewer	Pollo Connect
Push Notification	TUTK/RS
P/W Reset	Factory Reset: Press 10 seconds
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, EDID)
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*2
HDD	1 SATA HDD, up to 8TB
Input Voltage/Current	DC12V/2A
Power consumption	3.6W
Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F) Humidity: Less than 90%RH