



PLC-1508H1/PR-E

08 Channel DVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1508H1/PR-E

08 Channel DVR

Specifications:



Model	PLC-1508H1/PR-E
Inputs	8Mbps ~40Mbps IP Bandwidth max is 8Mbps, decrease one Analog channel can increase 4Mbps (default decoding performance 1080P 60fps)
Bandwidth out	56Mbps
Analog video-input	8CH inputs
IP Video Input	2ch, (only IP up to 10ch)
Composite Video Input	up to 10 Ch (Analog video + IP video)
Installation wizard	Yes
Compression	Audio: G.711a Video: H.264/H.265
Display resolution	5MP-Lite (1280*1944): 12fps, 1080P:15fps 1080N/720P/960H:30fps IP:1080P/720P Single IP channel preview up to 2MP 30 fps multi-channel preview only sub stream
Speed	5MP-Lite (1280*1944): 12fps (each Ch) 1080P (1920*1080) :15fps (each Ch) 720P:30fps (each Ch) 1080N-Model default 5MP-Lite (1280*1944): 12fps (each Ch) 1080N (960*1080) :30fps (each Ch) 720P:30fps (each Ch) IP:PAL:25fps (each Ch) / NTSC: 30fps (each Ch) Sub-stream PAL 704*576:10fps (each Ch) / NTSC : 704*480:10fps (each Ch)
Event	MD (Sensitivity Level 1~8), Video loss Email, Push notification to Mobile APP
Playback Function	Fast forward / backward (2x, 4x, 8x,16x), Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MP lite: 80fps 4MPlite: 120fps 1080P: 120fps 720P:120fps
UI/Monitoring Local	UI5.0
Mobile viewer	Pollo Connect
Push Notification	TUTK/RS
P/W Reset	Factory Reset: Press 10 seconds
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, EDID)
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*2
HDD	1 SATA HDD, up to 8TB
Input Voltage/Current	DC12V/2A
Power consumption	4W
Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F) Humidity: Less than 90%RH