



**PLC-422M-AU-IR3/PR**

**Bullet 2MP**



**Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-422M-AU-IR3/PR

### Bullet 2MP



### Specifications:

<b>Model</b>	<b>PLC-422M-AU-IR3/PR</b>
<b>Imaging Device</b>	1/2.7"
<b>Effective Pixels</b>	2MP1920(H)×1080(V)
<b>Scanning System</b>	Progressive CMOS
<b>Min. Illumination</b>	Colour 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
<b>Focal Length (Zoom Ratio)</b>	3.6mm
<b>Max. Aperture Ratio</b>	F No. 2.3±10%
<b>Angular Field of View</b>	H:86.1° V : 46° D : 104°
<b>Min. Object Distance</b>	2m
<b>Lens Type</b>	Fixed(M12)
<b>IR Viewable Length</b>	Up to 30m
<b>Camera Title</b>	On/Off
<b>Day &amp; Night</b>	IR cut filter with auto switch Day/Night/Auto/Schedule)
<b>Backlight Compensation</b>	Off/On (5 Zone)
<b>Wide Dynamic Range</b>	DWDR
<b>Digital Noise Reduction</b>	3D DNR
<b>Motion Detection</b>	Off/On (8 Level)
<b>Gain Control</b>	Auto
<b>White Balance</b>	Auto/Manual
<b>Electronic Shutter Speed</b>	1/5 ~ 1/20000s
<b>Flip / Mirror</b>	Flip/Rotation
<b>Alarm</b>	NO
<b>Audio</b>	Built-in microphone
<b>Hardware Reset</b>	Yes
<b>Ethernet</b>	RJ45(10/100BASE-T)
<b>Video Compression Format</b>	H.265/H.264
<b>Max. Resolution</b>	Main Stream 1080P(1920x1080) Sub Steam VGA (640x480)
<b>Max. Framerate</b>	50Hz: 25fps /1920x1080 20fps /640x480 60Hz: 30fps /1920x1080 20fps /640x480
<b>Video Quality Adjustment</b>	128Kbps ~ 4Mbps
<b>Bitrate control method</b>	CBR/VBR

<b>Streaming Capability</b>	Dual-Stream (Main/Sub)
<b>IP</b>	IPv4
<b>Protocol</b>	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
<b>Security</b>	IP address filter; complicated password; Authenticated username and password
<b>Streaming Method</b>	Unicast/Multicast
<b>Max. User Access</b>	Max 2 (admin+user)
<b>Application Programming Interface</b>	ONVIF
<b>Web Viewer</b>	IE8,9,10,11, Chrome 44/lower, Firefox 51/lower, Safari 11/lower,
<b>Operating Temperature / Humidity</b>	-30~+60°C/less than ≤ 95% RH
<b>Ingress Protection</b>	IP66
<b>Input Voltage / Current</b>	D12V/POE(IEEE802.3af)
<b>Power Consumption</b>	TBD
<b>Color / Material</b>	White/Metal
<b>Weight</b>	650g

**Dimensions:**
