



PLC-425M-AU-IR3/PM

Bullet 5MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-425M-AU-IR3/PM

Bullet 5MP



Specifications:

Model Name	PLC-425M-AU-IR3/PR
Imaging Device	1/2.7"
Effective Pixels	5MP 2592(H)×1944(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	3.6mm
Max. Aperture Ratio	F No. 1.6±5%
Angular Field of View	Horizontal:81°, Vertical:57°, Diagonal:108°
Min. Object Distance	0.2M
Lens Type	Fixed(M12)
IR Viewable Length	Up to 30m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch Day/Night/Auto/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual/Indoor
Electronic Shutter Speed	1/5 ~ 1/20000s
Flip / Mirror	Flip/Rotation
Audio	Built-in microphone
Hardware Reset	Yes
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264

Resolution	Main Stream 5MP (2592*1944), 4MP (2592x1520),3MP (2304x1296), 1080P(1920x1080), 720P(1280x720), Sub Stream 720P(1280x720), VGA (640x480), QVGA (320x240) Mobile Stream QVGA (320x240)
Max. Framerate	5MP ~ 20fps 4MP ~ 30fps
Video Quality Ajustment	8Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Triple-Stream (Main/Sub/Moile)
IP	IPv4
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Security	IP address filter; complicated password; Authenticated username and password
Streaming Method	Unicast/Multicast
Max. User Access	Max 7 (Admin+User)
Application Programming Interface	ONVIF (Profile S/G/T)
Web Viewer	IE8,9,10,11, Chrome 44/lower, Firefox 51/lower,
Operating Temperature / Humidity	-30~+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption	12V/2A
Color / Material	White/Metal
Weight	650g

Dimensions: