

pöllö 
Prime Series




2MP FULL COLOUR FHD CAMERA

PLC-322P-WR3/PM

www.pollo.net.au

info@pollo.net.au



Sensor



BLC



DWDR



Full-Color



Day&Night



Auto WB




Sync



AGC



IP67






Key Features:

- ✔ 1080P real-time image, high resolution, true colour
- ✔ AHD / TVI / CVI lossless HD video output
- ✔ Support 960H CVBS output
- ✔ CMOS progressive scan, perfectly capturing the moving object Support OSD menu
- ✔ High speed, long distance and real time transmission
- ✔ 24/7 full colour imaging
- ✔ LED can be turned on or off automatically
- ✔ Support noise reduction function
- ✔ 20 ~ 30m LED distance
- ✔ IP67
- ✔ Support COC

Dimensions:



Specifications:



Model	PLC-322P-WR3/PM
Image Sensor	1 / 2.8 "CMOS
Resolution	2MP
Image Size	1920 x 1080
Video Output	AHD / TVI /CVI/CVBS
Image System	PAL / NTSC
Electronic Shutter	Auto
LED Distance	20 ~30 m
Frame Rate	30fps(60Hz); 25fps (50Hz)
Min. Illumination	0 lux (LED ON)
Lens	2.8mm
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP 67
Function Control	OSD (COC Control)
Smart LED	Manual or Auto mode
ICR	NO
Digital WDR	Yes
Digital DNR	Yes, 2D DNR
AGC	Yes
Auto White Balance	Yes
BLC	Yes
HLC	Yes
Sharpness	Yes
Contrast	Yes
Image Setting	Yes
Defect Correction	Auto
Language	Chinese and English
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°
Power Supply	DC12V (± 15%)
Power Consumption	LED OFF: < 1W; LED ON: < 4W
Working Environment	- 30 °C ~ 50 °C, 10 % ~ 90 % (relative humidity)
Dimensions (mm)	162.1× 74.8× 73.8
Weight (net)	Approx. 0.37KG