

pöllö

Prime Series




2MP IP Camera

PLC-432P-AU-IR2/PM

www.pollo.net.au

info@pollo.net.au





Key Features:

- ✔ 2MP (1920 × 1080) H.265 coding.
- ✔ Max. resolution: 1920 × 1080.
- ✔ ICR auto switch, true day / night, ROI coding.
- ✔ 3D DNR, digital WDR, HLC, BLC, defog.
- ✔ 10~20m IR night view distance.
- ✔ DC12V/PoE power supply.
- ✔ 1CH built-in MIC.
- ✔ IP 67 ingress protection.
- ✔ Support dual streams.
- ✔ Support mobile surveillance by smart phones with iOS and Android OS.
- ✔ Intelligent analytics: video blur detection, scene change detection, line crossing detection and region intrusion detection.



Dimensions:





Specifications:

Model	PLC-432P-AU-IR2/PM
Image Sensor	1 / 2.8" CMOS
Image Size	1920×1080
Electronic Shutter	1 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0126lux @F1.2, AGC ON; 0 lux with IR 0.0462 lux @ F2.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F2.2, H. FoV: 102°; V. FoV:54.7°; D. FoV:124.4°
Focus	Fixed
Lens Mount	M12
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80°; Rotation: 0°~360°
Video Compression	H.265 / H.264
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF
Main Stream	60Hz : 1080P/720P(1~30fps); 50Hz : 1080P/720P(1~25fps)
Sub Stream	60Hz : D1/CIF(1~30fps); 50Hz: D1/CIF/(1~25fps)
Bit Rate	64 Kbps ~ 4 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Audio Compression	G711A/U
Network	RJ45
Video Output	No
Audio	1CH built-in MIC
Storage	No
Reset	No
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion detection

Intelligent Analytics	Region intrusion detection, video blur detection, scene change detection, line crossing detection
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE	Yes, IEEE802.3af
IR Distance	10 ~ 20m
Ingress Protection	IP67
Power Supply	DC12V/PoE
Power Consumption	< 4 W
Operating Environment	- 20 °C ~ 55 °C (-4°F~131°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 94.8 × 82.8
Weight (net)	Approx. 0.287KG
Installation	Ceiling mounting (Wall mounting available with the junction box and bracket)
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE (2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)