

pöllö 
Prime Series





8MP IP Camera

PLC-438M-MZK-IR5/PM

www.pollo.net.au

info@pollo.net.au







Key Features:

- ✔ H.265+/H.265/H.264+/H.264 coding
- ✔ Max. resolution: 8MP (3840 × 2160)
- ✔ ICR auto switch, true day / night vision
- ✔ 3D DNR, true WDR, HLC, BLC, smart IR and ROI coding
- ✔ Lens distortion correction supported
- ✔ 30~50m IR night view distance; Motorized zoom lens
- ✔ 1CH audio input; 1CH audio output; 1CH built-in MIC
- ✔ Built-in micro-SD card slot, up to 256GB
- ✔ DC12V/PoE power supply
- ✔ Support three streams
- ✔ IP 67&IK10
- ✔ Support mobile surveillance by smart phones with iOS and Android OS
- ✔ Intelligent analytics

Dimensions:



87.80mm



119.00mm



Specifications:

Model	PLC-438M-MZK-IR5/PM
Image Sensor	1 / 2.8 "CMOS
Image Size	3840×2160
Electronic Shutter	1 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.05 lux @ F1.4, AGC ON; 0 lux with IR 0.032 lux @ F1.2, AGC ON; 0 lux with IR
Lens	2.8~12mm@F1.4, motorized
Field of View	Horizontal:104.7°~32.5°; Vertical :72.2°~18.6°; Diagonal:112.2°~37°
Lens Mount	Φ14
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~345°; Tilt:0°~77°; Rotation: 0°~345°
Video Compression	H.265+ / H.265 / H.264+ / H.264
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	8MP (3840 × 2160), 6MP (3072 × 2048), 5MP (2592 × 1944), 4MP (2560 × 1440), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream	60Hz: 8MP/6MP(1~20fps), 5MP/4MP/1080P(1~30fps) 50Hz: 8MP/6MP(1~20fps), 5MP/4MP/1080P(1~25fps)
Sub Stream	720P/D1/CIF/480 × 240(60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream	D1/CIF/480 × 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~ 12 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	3 ROI, Each ROI to be configured separately
Network	RJ45
Video Output	CVBS output (BNC×1)
Audio	1CH audio input; 1CH audio output; 1CH built-in MIC
Alarm	1CH alarm input; 1CH alarm output
Storage	Built-in micro-SD card slot; up to 256GB
Reset	Yes
Remote Monitoring	Web browsing, CMS remote control

Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro-SD card storage
Smart Alarm	Motion detection; sensor alarm, SD card error; SD card full, IP address conflict, cable disconnection
Intelligent Analytics	Scene change, video blur detection, video colour cast detection, line crossing detection, intrusion detection
General function	Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction, etc.
IR Distance	30~50m
Protection Grade	IP 67&IK10
PoE	Yes (IEEE802.3af)
Power Supply	DC12V/PoE
Power Consumption	< 10.5W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 141 × 100.2
Weight (net)	Approx. 0.89KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE (2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)