



PLC-1516H1/PR

16 Channel DVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1516H1/PR

16 Channel DVR



Specifications:

Inputs	16Mbps ~32Mbps, IP Bandwidth default is 8Mbps,
Outgoing Bandwidth	64Mbps
Analog video-input	16CH inputs
IP Video Input	4ch, (only IP up to 20ch)
Composite Video Input	up to 20 ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog :5MP-Lite (1280*1944): 12fps;1080N/720P/960H IP :1080P/720P
HDMI	Analog :5MP-Lite (1280*1944): 12fps (each ch)1080N (960*1080) :15fps (each ch);720P:15fps (each ch)
Frame Rate	IP: PAL:25fps (each ch) / NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite:90fps (Max 6CH playback) ;1080P: 160fps (Max 8CH playback) ;720P:320fps Max 8CH playback)
BNC	N/A
VGA	N/A
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, EDID)
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*2(front)
Audio	N/A
HDD	1 SATA HDD, up to 8TB
RS485	N/A
Alarm Input/out	N/A
Dimension (WxDxH)	300X227X53mm
Input Voltage/Current	DC12V/2A
Power consumption (excluding hard disk)	8W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F) ,Humidity : Less than 90%RH