



PLC-1504H1/PR

04 Channel DVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1504H1/PR

04 Channel DVR



Specifications:

Model	PLC-1504H1/PR
Inputs	4Mbps ~20Mbps, IP Bandwidth deful is 4Mbps
out	32Mbps
Analog video-input	4CH inputs
IP Video Input	1ch, (only IP up to 5ch)
Composite Video Input	up to 5 ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog: 5MP-Lite:20fps ,4MP-Lite:30 fps,1080P/720P/960H:30fps IP:1080P/720P
Speed	Analog:5MP-Lite:20fps (each ch), 4MP-Lite:30fps (each ch), 1080P/720P:PAL:25fps (each ch)/NTSC:30fps (each ch) IP: PAL:25fps (each ch)/NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite:80fps ,4MPlite: 120fps ,1080P: 120fps,720P:120fps
VGA	N/A
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 ,EDID)
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*2(front)
Audio	N/A
HDD	1 SATA HDD, up to 8TB
Alarm Input/out	N/A
Dimension (WxDxH)	230*215*47mm
Input Voltage/Current	DC12V/2A
Power consumption (excluding hard disk)	3.6W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F) ,Humidity : Less than 90%RH