



PLC-1508H1/PR

08 Channel DVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1508H1/PR

08 Channel DVR

Specifications:



Model	PLC-1508H1/PR
Inputs	8Mbps ~40Mbps, IP Bandwidth max is 8Mbps
out	56Mbps
Analog video-input	8CH inputs
IP Video Input	2ch, (only IP up to 10ch)
Composite Video Input	up to 10 ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog: 5MP-Lite: 12fps (each ch),1080N (960*1080) :30fps (each ch),720P:30fps(each ch)
	IP:PAL:25fps (each ch) / NTSC: 30fps (each ch)
Speed	Analog:5MP-Lite (1280*1944): 12fps (each ch)
	1080P (1920*1080) :15fps (each ch)
	1080N (960*1080) :30fps (each ch),720P:30fps (each ch)
	IP: PAL:25fps (each ch)/NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8)
	Video loss Beep,
	Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x)
	Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite:48fps ,1080P: 60fps ,720P:120fps (Max 4CH playback)
VGA	N/A
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, EDID)
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*2(front)
Audio	N/A
HDD	1 SATA HDD, up to 8TB
Alarm Input/out	N/A
Dimension (WxDxH)	230*215*47mm
Input Voltage/Current	DC12V/2A
Power consumption (excluding hard disk)	4W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F), Humidity : Less than 90%RH