



PLC-1808H1/PR

8 Channel DVR



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-1808H1/PR

8 Channel DVR



Specifications:

Model	PLC-1808H1/PR
Inputs	24Mbps ~72Mbps, IP Bandwidth default is 24Mbps,
out	72Mbps
Analog video-input	8CH inputs
IP Video Input	4ch, (only IP up to 12ch)
Composite Video Input	up to 12ch (Analog video + IP video)
Compression	Audio: G.711a; Video: H.264/H.265
Display resolution	Analog: 8MP (15fps) ,5MP (20fps) ,4MP/1080P/720P/960H 30fps IP: 4K/4MP/1080P/720P
Speed	Analog :8MP:7fps (each ch), 5MP:12fps (each ch), 4MP:15fps (each ch), 1080P:PAL:25fps (each ch)/NTSC:30fps (each ch) IP:PAL:25fps (each ch)/NTSC: 30fps (each ch)
Event	MD (Sensitivity Level 1~8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	8MP: 60fps (Max 4CH playback) ,5MP: 96fps (Max 8CH playback) ,4MP: 120fps (Max 8CH playback) ,1080P: 240fps PID, LCD Factory Reset: Press 10 seconds
BNC	1 (704*576)
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
Ethernet	1 RJ45 10/100 Base-T1 RJ45 100/1000 Base-T
USB	USB2.0*1(front), USB2.0*1+(rear)
Audio	4 in / 1 out (Max 8 in /1 out optional,)
E-sata	1 optional, not supported by default
HDD	1 SATA HDD, up to 8TB default (Design reserved 2HDD)
RS485	1
Alarm Input/out	8 in /1 out optional, not supported by default
Dimension (WxDxH)	300X227X53mm
Power consumption (excluding hard disk)	11W
Operating Temperature/Humidity	Temperature : 0°C~+40°C (32°F ~ 104°F), Humidity : Less than 90%RH