



## PLC-322P-IR2/PR

Bullet 2 MP



### **Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLC-322P-IR2/PR

### Bullet 2 MP



#### Specifications:

<b>Model</b>	<b>PLC-322P-IR2/PR</b>
<b>Imaging Device</b>	1/3" Progressive CMOS
<b>Scanning System</b>	Progressive
<b>Min. Illumination</b>	0.05lux@F1.2 (AGC ON),0Lux with IR ON
<b>Video Output</b>	BNC
<b>Resolution</b>	2MP 1920 (H) ×1080 (V)
<b>Max. Framerate</b>	AHD/TVI/CVI: P/@25fps N/@30fps CVBS: 960H
<b>Focal Length (Zoom Ratio)</b>	3.6mm
<b>Max. Aperture Ratio</b>	F2.0
<b>Angular Field of View</b>	H:75.91° / V:55.35° / D:101.73°
<b>Min. Object Distance</b>	0.2m
<b>Lens Type</b>	Fixed lens
<b>Viewable length</b>	20m
<b>On Screen Display</b>	English
<b>IR Range</b>	10-20m
<b>Day &amp; Night</b>	Ext / Colour / B/W
<b>Backlight Compensation</b>	Off / User BLC
<b>Wide Dynamic Range</b>	D-WDR (Off/On)
<b>Digital Noise Reduction</b>	2D DNR
<b>Gain Control</b>	Auto
<b>White Balance</b>	ATW
<b>Electronic Shutter Speed</b>	Auto
<b>Reverse</b>	Mirror
<b>Remote control interface</b>	ACP (AHD Coax Protocol)
<b>Video Transmission Distance</b>	MAX 300m ( Cable: 5C 2V)
<b>Operating Temperature / Humidity</b>	-30°C ~ 50°C / 90%
<b>Ingress Protection</b>	IP66
<b>Input Voltage/Current</b>	12V DC
<b>Power Consumption</b>	IR ON: 3.5W, IR OFF: 0.5W
<b>Color / Material</b>	Plastic
<b>Weight</b>	380 g
<b>Safety</b>	CE LVD
<b>EMC</b>	CE EMC、 FCC
<b>ROHS</b>	RoHS2.0

Dimensions:

