



PLC-325P-AU-IR3/PR

Bullet 5MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-325P-AU-IR3/PR

Bullet 5MP



Specifications:

Model	PLC-325P-AU-IR3/PR
Imaging Device	1/2.7" Progressive CMOS
Total Pixels	2608 (H) ×1960 (V)
Effective Pixels	2608 (H) ×1960 (V)
Scanning System	Internal
Min. Illumination	0.05lux@F1.2 (AGC ON),0Lux with IR ON
Video Output	BNC
Resolution	5MP 2592 (H) ×1944 (V)
Max, Framerate	5AHD/5TVI: 5MP@20fps 4AHD/4CVI/4TVI: P@25fps N@30fps CVBS: 960H
Focal Length (Zoom Ratio)	3.6mm
Max. Aperture Ratio	F2.2
Angular Field of View	H:91.3° / V:46.1° / D:109.6°
Min. Object Distance	0.8m
Lens Type	Fixed lens
Audio	Audio over coaxial
Audio Range	7m
IR Distance	30m
On Screen Display	English
Day & Night	Auto / Ext / Colour / B/W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	N/A
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote control interface	ACP (AHD Coax Protocol)
Video Transmission Distance	MAX 300m (Cable: 5C 2V)
Operating Temperature / Humidity	-30°C ~ 50°C / 90%

Ingress Protection	IP66
Input Voltage/Current	12V DC
Power Consumption	IR OFF ≤1W, IR ON ≤4W
Colour / Material	White / plastic
Weight	380 g
Safety	CE LVD
EMC	CE EMC, FCC
ROHS	RoHS2.0

Dimensions:

